

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TR. CASE*
(Other instructions on re-
verse side)

LEASE DESIGNATION AND SERIAL NO.
hc-058697B

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injection	7. UNIT AGREEMENT NAME McA Unit
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME McA Unit Bty 4
3. ADDRESS OF OPERATOR PO Box 460, Hobbs, NM 88240	9. WELL NO. No. 197
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit Keller h	10. FIELD AND POOL, OR WILDCAT McA Unit Bty 4
14. PERMIT NO. 30-025-0833600	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30 T. 7S, R. 33E
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH hca
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETION ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/13/89 Notified BLM prior to RU.

Breakdown wellhead, install BOP. Ran in hole to top of CIBP. Spd 25 sx cnt. on top of CIBP. hoed hole w/mud. Start out of hole. Circ. between 7" + 8-5/8" to surface next day. Went in hole w/4" perf gun at 1280'. Picked up 1 ft. cnt. CAS annulus from 0-1280'. Open 7" + 8-5/8" annulus to surface valve. Pump 115 sx down 7" string + circ. to surface. Rig down. Ered P-A marker. Restore location.

18. I hereby certify that the foregoing is true and correct

SIGNED W W Baker W W Baker

TITLE Administrative Supervisor

DATE 1/24/90

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE 2-26-90

Approved as to plugging of the well bore,
Liability on the part of the operator and
surface owner to be maintained.

*See Instructions on Reverse Side