1CR

NEW MEXICO STATE LAND OFFICE SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST NOTICE OF INTENTION TO TEST WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in triplicate.

Dear Sir: You are hereby notified that we intend to test the shut- Vell No. 1 in N.V.1/4 of Sec. 24 M. M. P. M., Hobbs Oil Field The method used in placing the cement was as follows Fluid level will be bailed to a depth of 2 hours before your inspection. Adjacent property owners have been notified as follows Additional information: 200 lbs. pressure held on easing for 30 min Approved 19 Sincerel Except as follows:	for water in State "D" 18S , R. 37E Lea County, cemented in Sandy Line y-9 19 34 cement were used. Halliburton Process
ear Sir: You are hereby notified that we intend to test the shut- fell No. 1 in N.V.1/4 of Sec. 24 M. P. M., Robbs Oil Field 9-12 19 34 7 in. 24 lb. casing we remation at a depth of feet on 250 sacks of El Tore The method used in placing the cement was as follows Fluid level will be bailed to a depth of 2 hours before your inspection. Adjacent property owners have been notified as follows at Texas and Pacific Goal & Oil Company. Additional information: 300 lbs. pressure held on casing for 30 min Except as follows: By Sincerely SHELL 19	for water in State "D" 18S , R. 37E Lea County, cemented in Sandy Line y-9 19 34 cement were used. Halliburton Process
You are hereby notified that we intend to test the shut- ell No 1 in N.W.1/4 of Sec. 24 M. P. M., Hobbs Oil Field 9-12 19 34. 7 in. 24 lb. casing we remation at a depth of sacks of 11 Toro The method used in placing the cement was as follows Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows d Texas and Pacific Coal & Oil Company. Additional information: 200 lbs. pressure held on casing for 30 min Approved 19 Sincerel Except as follows:	Lea County, cemented in Sandy Line y-9 19 34 cement were used. Halliburton Process
M. P. M., Soli Field 9-12 19 34 7 in. 24 1b. casing was a sacks of The method used in placing the cement was as follows Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows Texas and Pacific Coal & Oil Company. Additional information: 350 Additional information: 360 371 382 4030 582 Fluid level was as follows Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows 46 472 473 484 4930 Feet on 4930 Fluid level was as follows Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows 47 48 49 49 59 59 50 50 50 50 50 50 50 5	Lea County, cemented in Sandy Line y-9 19 34 cement were used. Halliburton Process
M. P. M., 9-12 19 34 7 in. 24 1b. casing warmation at a depth of sacks of The method used in placing the cement was as follows Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows Texas and Pacific Coal & Oil Company. Additional information: 30 15 31 32 34 40 40 40 40 50 60 60 60 60 60 60 60 60 6	County, cemented in Sandy Line p-9 19 34 cement were used. Halliburton Process
The method used in placing the cement was as follows Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows Texas and Pacific Coal & Oil Company. Additional information: OO lbs. pressure held on casing for 30 min typeroved Except as follows: Sincerels SHELL By	Halliburton Process
The method used in placing the cement was as follows Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows Texas and Pacific Coal & Oil Company. Additional information: OO lbs. pressure held on casing for 30 min hours before your inspection. Sincerels except as follows:	Halliburton Process
The method used in placing the cement was as follows Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows Texas and Pacific Coal & Oil Company. Additional information: OO lbs. pressure held on casing for 30 min hours before your inspection. Sincerels except as follows:	Halliburton Process
The method used in placing the cement was as follows Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows Texas and Pacific Coal & Oil Company. Additional information: OO lbs. pressure held on casing for 30 min approved Opproved Sincerel Except as follows: By	Halliburton Process
Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as followed Texas and Pacific Coal & Oil Company. Additional information: OO lbs. pressure held on casing for 30 min approved	
Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as followed Texas and Pacific Goal & Oil Company. Additional information: OO lbs. pressure held on casing for 30 minutes a property owners have been notified as follows: Sincerel Shrill By	
pproved 19 Sincerely sept as follows: By	
Except as follows: By	
Position	STROLEUM CORPORATION
1 0,1010	STROLEUM CORPORATION Company of Operator
Send co	Company of Operator
Name	Gompan Operator
Address	District Engineer
State Goologist or Oil and Gas Inspector.	District Ingineer munication regarding well to

(2) 2000年 (2) 2 THE THE REPORT THAT OF THE ASSET

٠,

. . .

And Control of the Co

 $\mathbf{r} = \mathbf{r} \cdot \mathbf{r} \cdot$

 $\mathbf{x} = \mathbf{x} \mathbf{x}^{T} + \mathbf{x}^{T}$

3.5.

James Commence of

1.00

t ·