NEW MEXICO STATE LAND OFFICE OFFICE OF THE STATE GEOLOGIST

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the State Geologist or proper Oil and Gas Inspector at least five days before the work specified is to begin. A copy will be returned to the sender on which will be given the approval with any modifications considered advisable or the rejection by the State Geologist or Oil and Gas Inspector of the plan submitted. The plan as approved should be followed and work should not begin until approval is obtained

		e of notice	OF IMPENTION TO PHILL OR
NOTICE OF INTENT	TION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
	TION TO REPAIR WELL	X	
NOTICE OF INTENT	TION TO DEEPEN WELL		
			Johns New Meyico, March. A 1934
			lobbs, New Mexico, March 3, 1934
r. J. D. Hunt	er State Ced	16 913 t, 0 1]	& Gas Inspector
_			
Following is a	notice of intention to do	certain w	ork as described below at the Sheel.
etroleum Cor	p., H. D.McKinle	ey "A"	Well No. 2 in SE 1/4
CMPANY OR OPERATOR	T. 18S, R	? 38 €	, N. M. P. M.,
T Deciment			ounty.
)il Field,		T DDADO	SED PLAN OF WORK
roposed to reproximately	epair the productions of the hole. The	ing whi commer e well	oil into the tubing. It is then te lime Section by placing cial Hydrochloric Acid Solution will then be shut in for about
roposed to reproximately the bottom chours before is recommentally of the commental comments are commentally of the comments are commentally of the comments are commentally of the comments are comments.	pair the product 1000 gailons of of the hole. The re it is placed anded that this was fiset wells which	commer e well back on ell be h has b	oil into the tubing. It is then te lime Section by placing cial Hydrochloric Acid Solution will then be shut in for about production. acid treated to prevent lease seen acid treated.
coposed to reproximately the bottom chours before the recommentation of the recommendation of the recommendati	epair the product 1000 gailons of of the hole. The re it is placed anded that this was fiset wells which	commer e well back on ell be h has b	oil into the tubing. It is then te lime Section by placing cial Hydrochloric Acid Solution will then be shut in for about production. acid treated to prevent lease seen acid treated. Shell Petroleum Corporation
roposed to reproximately the bottom chours before is recommentally of the commental comments are commentally of the comments are commentally of the comments are commentally of the comments are comments.	epair the product 1000 gailons of of the hole. The re it is placed anded that this was fiset wells which	commer e well back on ell be h has b	oil into the tubing. It is then te lime Section by placing cial Hydrochloric Acid Solution will then be shut in for about production. acid treated to prevent lease een acid treated. Shell Petroleum Corporation ByH. F. Winham Definition
coposed to reproximately the bottom chours before the recommentation of the recommendation of the recommendati	epair the product 1000 gailons of of the hole. The re it is placed anded that this was fiset wells which	commer e well back on ell be h has b	oil into the tubing. It is then te lime Section by placing cial Hydrochloric Acid Solution will then be shut in for about production. acid treated to prevent lease seen acid treated.
Approved	epair the product 1000 gailons of of the hole. The re it is placed anded that this was fiset wells which	commer e well back on ell be h has b	oil into the tubing. It is then te lime Section by placing cial Hydrochloric Acid Solution will then be shut in for about production. acid treated to prevent lease seen acid treated. Shell Petroleum Cerporation ByH. F. Winham My Jack Position Div. Engineer Send communications regarding well to