Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

turned to t structions					a 1. 3 - 11	The second secon
			s, New Mexico	July Jace	27, 1947	201 1 12 1
ta Fe, Ne tlemen:	RVATION COL	MMISSION,	•	ince	* 1	Date, A.
ou are h	ereby notified	that it is our inter	ition 'to 'commence	the drilling of a v	vell to be known a	us
hell Of	11 Company	Incorporated	H.D. McKinl	67 777	11 No A-9	
$\frac{\text{Comp}}{\text{Sec.}}$	pany or Operato	3-S R 38-12	, N. M. P.M.,	Lease Boyers	7.	
	N.	The well is	660 feet (N) (T) of the So	Field,	County
		(E.) (12.)	of the West 1	ine of Sec. 19	. T 18-8. R 3	8-E
			on from section or o			
			the oil and gas le			
	 		land the owner is			
 		Address				
		If governme	ent land the permi			
		1 1				
-		The lessee i	s Shell 011	Company, Inc	rporated	
	A 640 ACRES	Address	Box 1509 M10	dland, Texas		
OCATE V						
	WELL CORREC	we propose	to drill well with d	rilling equipment	as follows:	
	ional Rota	ry Drilling R	le	rilling equipment	as follows:	
status of	ional Rota	ry Drilling R	nce with Rule 39 o	rilling equipment	as follows:	of the Commission
status of follows	a bond for the	ry Drilling R	ace with Rule 39 o	trilling equipment	as follows:	of the Commission
status of follows propose t	a bond for the	ry Drilling R: is well in conformation owing strings of ca	ace with Rule 39 o	trilling equipment	as follows:	of the Commission
status of follows propose t	a bond for the	ry Drilling R: is well in conformation owing strings of ca	ace with Rule 39 o	trilling equipment	as follows: s and Regulations of indicated: Landed or	of the Commission
status of s follows propose t Size of Hole	a bond for the to use the foll Size of Casing	ry Drilling Rissis well in conformation owing strings of care weight Per Foot	nce with Rule 39 of asing and to land New or Second Hand	f the General Rules or cement them as	as follows: s and Regulations of indicated: Landed or Cemented	of the Commission Sacks Cement
status of s follows propose t Size of Hole	a bond for the size of Casing 8 5/8*	ry Drilling R	ace with Rule 39 o	f the General Rules	as follows: s and Regulations of indicated: Landed or	of the Commission
status of follows propose t Size of Hole	a bond for the to use the foll Size of Casing	ry Drilling Rissis well in conformation owing strings of care weight Per Foot	nce with Rule 39 of asing and to land New or Second Hand	or cement them as Depth 400 Approx. 317 on top of 1	s and Regulations of indicated: Landed or Cemented Cemented	of the Commission Sacks Cement
status of follows propose of Hole 7/8* anges in	a bond for the to use the following Size of Casing 8 5/8* 4 1/2* the above pla	we propose Ty Drilling R: is well in conformation owing strings of ca Weight Per Foot 32† 9 1/2‡ n become advisable	nce with Rule 39 of asing and to land New or Second Hand New New New New New New New Ne	or cement them as Depth 400 Approx. 317 on top of I Sand u before cementin	s and Regulations of indicated: Landed or Cemented Cemented 5 cemented	Sacks Cement To surface
status of follows propose to size of Hole 7/8* anges in the first	a bond for the size of Casing 8 5/8* 4 1/2* the above pla productive oil	ry Drilling R. is well in conformation owing strings of ca Weight Per Foot 32# 9 1/2# n become advisable or gas sand should	nce with Rule 39 of asing and to land New or Second Hand New New New New Second Hand New New Actual Actua	or cement them as Depth 400 Approx. 317 on top of I Sand u before cementin of about 3175	s and Regulations of indicated: Landed or Cemented Cemented Cemented overs g or landing casin—feet.	Sacks Cement To surface To top of
follows propose to size of Hole 7/8* anges in the first tional interests	a bond for the size of Casing 8 5/8* 4 1/2* the above pla productive oil formation: B	ry Drilling R. is well in conformation owing strings of car Weight Per Foot 32† 9 1/2‡ n become advisable or gas sand should sefore running	nce with Rule 39 of asing and to land New or Second Hand New We will notify you do occur at a depth	or cement them as Depth 400 Approx. 317 on top of I Sand u before cementin of about 3175	Landed or Cemented Cemented Cemented overs g or landing casin feet.	Sacks Cement To surface To top of
follows or follows or follows or follows or follows of Hole or first anges in the first cional interest the first th	sional Rota a bond for the to use the foll Size of Casing 8 5/8* 4 1/2* the above pla productive oil formation: Be 1/2-inch	we propose Ty Drilling R: is well in conformation owing strings of car Weight Per Foot 32 9 1/2 n become advisable or gas sand should efore running casing to the	nce with Rule 39 of asing and to land New or Second Hand New We will notify you do occur at a depth	or cement them as Depth 400 Approx. 317 on top of I Sand u before cementin of about 3175	Landed or Cemented Cemented Cemented overs g or landing casin feet.	Sacks Cement To surface To top of
follows propose to dize of Hole 7/8* anges in the first tional int	sional Rota a bond for the to use the foll Size of Casing 8 5/8* 4 1/2* the above pla productive oil formation: Be 1/2-inch survey wil:	we propose ry Drilling R: is well in conformat owing strings of ca Weight Per Foot 32† 9 1/2‡ n become advisable or gas sand should efore running casing to the 1 be run.	nce with Rule 39 of asing and to land New or Second Hand New New New Item Tem Tem Tem Tem Tem Tem Tem	or cement them as Depth 400 Approx. 317 on top of I Sand u before cementin of about 3175	Landed or Cemented Cemented Cemented overs g or landing casin feet.	Sacks Cement To surface To top of
follows propose of Hole 7/8* anges in the first tional interest the first tional interest the first than the first than the first the	sional Rota a bond for the to use the foll Size of Casing 8 5/8* 4 1/2* the above pla productive oil formation: Be 1/2-inch survey wil:	we propose ry Drilling R: is well in conformat owing strings of ca Weight Per Foot 32† 9 1/2‡ n become advisable or gas sand should efore running casing to the 1 be run.	nce with Rule 39 of asing and to land New or Second Hand New New New Iew Iew Iew Iew Iew	or cement them as Depth 400 Approx. 317 on top of I Sand u before cementin of about 3175 propose to r	Landed or Cemented Cemented Cemented overs g or landing casin feet.	Sacks Cement To surface To top of
status of follows propose of Hole 7/8 anges in the first tional interest to the first to the f	sional Rota a bond for the to use the foll Size of Casing 8 5/8* 4 1/2* the above pla productive oil formation: B 1/2-inch survey will	we propose Ty Drilling R: is well in conformation owing strings of car Weight Per Foot 32 9 1/2 n become advisable or gas sand should efore running casing to the	nce with Rule 39 of asing and to land New or Second Hand New New New Tev Second Hand New Tev Tev Second Hand Se	or cement them as Depth 400 Approx. 317 on top of I Sand u before cementin of about 3175 propose to r it. Followin	Landed or Cemented Cemented Cemented overs g or landing casin—feet. un Caliper Sug Cementing,	Sacks Cement To surface To top of To top and a temp-
status of follows propose of Hole 7/8* anges in the first tional intent 4	sional Rota a bond for the to use the foll Size of Casing 8 5/8* 4 1/2* the above pla productive oil formation: B 1/2-inch survey will	we propose ry Drilling R: is well in conformat owing strings of ca Weight Per Foot 32† 9 1/2‡ n become advisable or gas sand should efore running casing to the 1 be run.	nce with Rule 39 of asing and to land New or Second Hand New New New Tev Second Hand New Tev Tev Second Hand Se	or cement them as Depth 400 Approx. 317 on top of I Sand u before cementin of about 3175 propose to r it. Followin	Landed or Cemented Cemented Cemented overs g or landing casin—feet. un Caliper Sug Cementing,	Sacks Cement To surface To top of To top and a temp-
follows propose in fize of Hole 7/8 anges in the first tional ini the first	sional Rota a bond for the to use the foll Size of Casing 8 5/8* 4 1/2* the above pla productive oil formation: B 1/2-inch survey will	we propose ry Drilling R: is well in conformat owing strings of ca Weight Per Foot 32† 9 1/2‡ n become advisable or gas sand should efore running casing to the 1 be run.	nce with Rule 39 of asing and to land New or Second Hand New Hew we will notify your occur at a depth oil string we top of the sa	or cement them as Depth 400 Approx. 317 on top of I Sand u before cementin of about 3175 propose to r it. Followin	Landed or Cemented Cemented Cemented Cemented overs g or landing casin—feet. un Caliper Sug Cementing,	Sacks Cement To surface To top of The contract of the contra
follows propose in fize of Hole 7/8 anges in the first tional ini the first	sional Rota a bond for the to use the foll Size of Casing 8 5/8* 4 1/2* the above pla productive oil formation: B 1/2-inch survey will	we propose ry Drilling R: is well in conformat owing strings of ca Weight Per Foot 32† 9 1/2‡ n become advisable or gas sand should efore running casing to the 1 be run.	nce with Rule 39 of asing and to land New or Second Hand New New New Item Them Them	Trilling equipment of the General Rule or cement them as Depth 400 Approx. 317 on top of I sand u before cementin of about 3175 propose to relative to the sand of the sand o	Landed or Cemented Cemented Cemented S cemented overs g or landing casin—feet. un Caliper Sug Cementing,	Sacks Cement To surface To top of To top and a temp-
status of follows propose of Hole 7/8 anges in the first tional interest to the first to the f	sional Rota a bond for the to use the foll Size of Casing 8 5/8* 4 1/2* the above pla productive oil formation: B 1/2-inch survey will	we propose ry Drilling R: is well in conformat owing strings of ca Weight Per Foot 32† 9 1/2‡ n become advisable or gas sand should efore running casing to the 1 be run.	nce with Rule 39 of asing and to land New or Second Hand New New We will notify your occur at a depth oil string we top of the sa 19	Trilling equipment of the General Rule or cement them as Depth 400 Approx. 317 on top of I sand u before cementin of about 3175 propose to relative to the sand of the sand o	Landed or Cemented Cemented Cemented S cemented overs g or landing casin—feet. un Caliper Sug cementing, and Regulations of the comment of the comment of the comment of the cement of the ceme	Sacks Cement To surface To top of To top and a temp-

Address Box 1'57 Hobbs, New Mexico:

and the second of the second o

Mary Markage for