

DISTRICT

1625 N. French Drive, Hobbs, NM 88240

OIL CONSERVATION DIVISION

310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO.	30-025-12497
5. Indicate Type of Lease	FED <input type="checkbox"/> STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	NORTH HOBBS (G/SA) UNIT
SECTION	28
8. Well No.	31
9. Pool name or Wildcat	HOBBS (G/SA)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101 FOR SUCH PROPOSALS.)	
1. Type of Well:	Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>
2. Name of Operator	OCCIDENTAL PERMIAM, LTD.
3. Address of Operator	1017 W STANOLIND RD.
4. Well Location	Unit Letter <u>L</u> : <u>2310</u> Feet From The <u>SOUTH</u> Line and <u>330</u> Feet From The <u>WEST</u> Line Section <u>28</u> Township <u>18-S</u> Range <u>38-E</u> LEA County
10. Elevation (Show whether D, RKB, RT GR, etc.)	3649' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG & ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER: <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER: <input checked="" type="checkbox"/> CONVERT TO INJECTOR

12. Describe Proposed or Completed Operations (Clearly state all pertinent details and give pertinent dates, including estimated completion date and proposed work) SEE RULE 1103.

RUPU. LAY DOWN RODS AND PUMP.
TEST SQZ PERFS @4124' - 4131'. TEST OK.
ACID TREAT OPEN HOLE WITH 2500 G 15% HCL ACID.
PERFORATE 4160' - 4180'. 2 JSPF AND 180 DEGREE PHASED.
ACIDIZE NEW PERFS W/1600 G 15% HCL ACID.
SET 5.5" GUIBERSON UNI VI PKR @4000'.
TEST CSG TO 540 PSI FOR 30 MIN AND CHART FOR THE NMOO.
CIRC CSG W/INHIBITED FLUID.
RDPU. CLEAN LOCATION.
WELL IS ON INJECTION.

RIG UP DATE: 09/18/00
RIG-DOWN DATE: 09/22/00

I hereby certify that the information above is true and complete to the best of my knowledge and belief	
SIGNATURE <u>Robert N. Gilbert</u>	TITLE <u>COMPLETION SPECIALIST</u> DATE <u>10/05/2000</u>
TYPE OR PRINT NAME <u>R.N. GILBERT</u>	TELEPHONE <u>505/397-8206</u>
(This space for State Use)	

APPROVED BY _____	TITLE _____	DATE <u>001 12 2000</u>
CONDITIONS OF APPROVAL IF ANY:		

ICSN

9

