

WTAPE		
Je		
S.C.S.		
LAND OFFICE		
OPERATOR		

3a. Indicate Type of Lease	State ☐	Fee ☒
3. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

Oil Well ☒	Gas Well ☐	Other ☐
--	-----------------------------------	--------------------------------

Name of Operator

Shell Oil Company

Address of Operator

P.O. Box 991 Houston, TX 77001

Location of Well

UNIT LETTER G 2310 FEET FROM THE north LINE AND 2310 FEET FROMTHE east LINE, SECTION 34 TOWNSHIP 18S RANGE 38E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3635' GR

7. Unit Agreement Name

N. Hobbs (G/SA) Unit

8. Farm or Lease Name

N. Hobbs (G/SA) Unit Sec 3

9. Well No.

321

10. Field and Pool, or Wildcat

Hobbs (GB/SA)

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

WELL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOBS ☐

OTHER Install submersible pump ☒

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1102.

4-29-80: RUPU (DA&S). Pld & laid down rods. Killed well w/200 bbls 2% KCl wtr. Installed BOP. Pld 143 jts 2 7/8" 10V tbg. Ran (Baker) Model-C RBP & set @2512'. Loaded csg w/2% KCl wtr. Pld tbg.

5-1-80: Ran retrieving head & retrieved (Baker) RBP. Ran Reda equipment as follows: ran BH pressure sensors seal #45-296119 @4006'-4011'. Ran Reda motor Type HU-12-69-BUT 60 HP, 970 volts, 40 amps, 3990'-4006', Reda protector Type SB-PS @3986'-3990', Reda gas separator Type 65 @3982'-3986', Reda pump Type B28, Stages 87 & 105, 65X-DT-65BFL-CT @3965-3982', 5 jts 2 7/8" D&V tbg, 3816-3965', Reda check & bleed collars @3815-3816', all 130 jts 2 7/8" D&V tbg 3815'. Hung well on. SDON.

5-2-80: Pumped well to battery for 6 hrs @rate of 400 bbls fluid per day.

8. I hereby certify that the information above is true and complete to the best of my knowledge.

SIGNED A.J. Fore TITLE Senior Engineering Technician DATE 6-17-80

APPROVED BY Jerry Fore TITLE DATE JUL 5 1980

CONDITIONS OF APPROVAL: None