

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL  
(Other Instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT--" for such proposals.)

OIL ☐ WELL GAS ☐ WELL OTHER ☐ Dry Hole - Henderson, Dexter, Black

2. NAME OF OPERATOR

OXY USA INC.

3. ADDRESS OF OPERATOR

P.O. BOX 50250 MIDLAND, TX 79710

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface

? - 330 FSL 330 FWL Sec 34 T17S R33E

5. LEASE DESIGNATION AND SERIAL NO.

NMLC062391

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Wyatt

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Corbin Queen

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 34 T17S R33E

14. PERMIT NO.

9001500000

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4000

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notices, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Re-plug Well Per R-9337

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and five pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD - 5370' This well was Re-entered & Plugged & Abandoned as follows:

10/25/91, Build loc, dig cellar & pit, install anchors. Dig out cellar to 30', set 30' of 30" conductor, backfill cellar. Drill 26" hole to 65' & set 20" conductor pipe @ 65', cmt w/ redi-mix. RIH w/ 17-1/2" bit & drill to 283' & mill to 828' in 8 days, recovering junk from hole. RIH w/ 7 jts 13-3/8" 72# N-80 csg & set @ 283'. Cement w/ 300 sx Cl C cmt + 2% CaCl<sub>2</sub>, cmt did not circ, WOC. RIH w/ 1" tbg down 13-3/8" csg X 20" conductor & annulus, tag TOC @ 165'. Cement w/ 353 sx Cl C cmt w/ 2% CaCl<sub>2</sub>, circ 5sx cmt to pit. RIH w/ 12" bit & drill out to 283', test csg to 600#, held OK.

RIH w/ 5-1/2" bit or 4-3/4" mill & drill, mill or clean out to 2575' in 13 days. Circ hole w/ 9.5 ppg mud-laden fluid, spot 150 sx Cl C w/ 2% CaCl<sub>2</sub> cmt plug, POOH, WOC 4 hrs. RIH & tag plug @ 2140', spot 50 sx Cl C cmt plug. POOH to 1730', spot 22 sx Cl C cmt plug (50' in & 50' out of 6-5/8" csg @ 1680'). POOH to 1550', spot 60 sx Cl C cmt plug (50' in & 50' out of 10" csg @ 1500'). POOH to 330', spot 94 sx Cl C cmt plug (50' in & 50' out of 13-3/8" csg stub @ 280'), WOC, SION. Work witnessed by L.W. Hill - NMOCD & BLM notified but did not witness. RIH & tag cmt @ 178', POOH to 60' & spot 50 sx Cl C cmt plug to surface. Cut off wellhead, install dry hole marker & clean location. Well P&A'd 11/29/91.

Approved by \_\_\_\_\_  
Liberty of the \_\_\_\_\_  
surface restoration is \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineering Advisor

DATE

12-6-91

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

12-20-91

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side