

LOG OF WELL

SHEET No. 2

District	Owner	Farm	Well No.			
FORMATION	BOTTOM	AMOUNT	COLOR	HARD or SOFT	DEPTH CORES TAKEN	REMARKS
Sand	4631	16				Top white dolomite section
White dolomite	4650	19				
Sandy lime	4660	10				
Light grey lime	4703	43				
Brown sandy lime,	4718	15				4000' of oil in hole
White lime	4840	122				Increase in oil 4745
SAMPLE LOG						
Lime	2752		White			
Lime, sandy	4912	2160	Grey & Blue			
Lime, sandy	4926	14				
Lime	4936	10	Grey			
Lime	4948	12	Dark			
Lime	4953	5	Grey			
Lime	4958	5	Dark			
Lime	4970	12	White	Hard		
Lime, broken	5060	90	Dark			
Lime	5071	11	Light	Hard		
Slate	5085	14	Black			
Lime	5093	8	Dark			
Lime, sandy	5102	9		Hard		
Lime	5123	11	Dark	Hard		
Lime, fine	5182	59	Brown			
Lime, fine	5200	18	Black			
Lime, fine	5236	36	Dark			
Lime	5246	10	grey			
Lime, shaley	5253	7	Dark			
Lime	5267	14	Grey			
Lime, shelly	5277	10	Brown			
Lime	5291	14	Grey			
Lime	5325	34	Grey	Hard		
Sand <u>Total Depth</u>	5329	4				1/2 bailer salt water per hour.

WFB-BCC
cc AEW

R.L.Halley (State Oil & Gas Inspector) Carlsbad, New Mexico

WFB-RCC

cc AEW

R.L.Halley (State Oil & Gas Inspector) Carlsbad, New Mexico