

10. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State ☒ Fee ☐	
5. State Oil & Gas Lease No. B-936	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT -- (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator EXXON CORPORATION	8. Farm or Lease Name NEW MEXICO "80" STATE
3. Address of Operator P.O. BOX 1600, MIDLAND, TEXAS 79701	9. Well No. 6
4. Location of Well UNIT LETTER O 822 FEET FROM THE SOUTH LINE AND 1838 FEET FROM THE EAST LINE, SECTION 12 TOWNSHIP 18-S RANGE 34-E N.M.P.M.	10. Field and Pool, or Wildcat VACUUM ABO
15. Elevation (Show whether DF, RT, GR, etc.) DF 3992	12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. SET WIRELINE BRIDGE PLUG AT 8860' AND CAP WITH 35' CEMENT (3 SX) USING A WIRELINE DUMP BAILEY.
2. LOAD WELL WITH 9.5#/GAL MUD LADEN BRINE. MUD CONSISTENCY TO BE OBTAINED BY MIXING 25 SX GEL PER 100 BBLs WTR.
3. FREE POINT AND CUT 4 1/2" CSG.
4. SPOT CEMENT PLUGS THROUGH 4 1/2" CSG. USING 9.5#/GAL MUD LADEN BRINE AS FOLLOWS:
100' PLUG W/35 SX ABOVE 4 1/2" CSG STUB (APPROX. 4100-4200').
100' PLUG W/35 SX ACROSS 8 5/8" CSG. SHOE (3350-3450').
5. FREE POINT, CUT AND PULL 8 5/8" CSG.
6. SPOT CEMENT PLUGS THRU TBG. USING 9.5#/GAL MUD LADEN BRINE AS FOLLOWS:
100' PLUG W/75 SX ACROSS 8 5/8" CSG. STUB (APPROX. 2150-2250').
100' PLUG W/75 SX ACROSS 13 3/8" CSG. SHOE (270-370').
10' PLUG AT SURFACE.
7. RIG WELLHEAD FOR ABANDONMENT.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

[Signature]

TITLE

UNIT HEAD

DATE

2-28-74

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: