

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-1431-3

SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State WM "E"
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 2
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>31</u> TOWNSHIP <u>18-S</u> RANGE <u>37-E</u> NMPM.	10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3749' DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Test Drinkard zone</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

July 1976:

Pulled rods, pump & tbg. Ran GR depth control log, gauge ring and junk basket & checked bottom at 7245'. Set Baker CI bridge plug in 5-1/2" csg. at 7245'. Perf. 5-1/2" csg. opposite Drinkard zone fr. 7040' to 7227'. Ran pkr. on 2-7/8" tbg. & set pkr. at 6932' and acidized w/3000 gal. 15% NE acid using ball sealers. Swabbd back load. Pulled & laid down 2-7/8" tbg. TA.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E.B. Fisher</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>4-5-77</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE <u>Dist 1, Supv.</u>	DATE <u>8/1/77 (11-)</u>
CONDITIONS OF APPROVAL, IF ANY:		