

Form 9-381a  
(Feb. 1951)**APPROVED****APR 12 1963**  
**RONNIE E. SHOOK**  
**ACTING DISTRICT ENGINEER**

(SUBMIT IN TRIPLICATE)

**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**GEOLOGICAL SURVEY****APR 22 AM 11 23**Budget Bureau No. 42-R358.4.  
Form Approved.Land Office **New Mexico**Lease No. **0 175774**

Unit

**RECEIVED**  
**APR 15 1963****O. C. C.**  
**ARTESIA, OFFICE****SUNDRY NOTICES AND REPORTS ON WELLS**

|  |  |                                     |
|--|--|-------------------------------------|
| NOTICE OF INTENTION TO DRILL                   | SUBSEQUENT REPORT OF WATER SHUT-OFF        | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO CHANGE PLANS            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |                                     |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF     | SUBSEQUENT REPORT OF ALTERING CASING       |                                     |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |                                     |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE        | SUBSEQUENT REPORT OF ABANDONMENT           |                                     |
| NOTICE OF INTENTION TO PULL OR ALTER CASING    | SUPPLEMENTARY WELL HISTORY                 |                                     |
| NOTICE OF INTENTION TO ABANDON WELL            |  |                                     |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Plains Unit

April 5, 1963

Well No. 2 is located 1980 ft. from N line and 660 ft. from W line of sec. 28SW/4, NW/4, Sec. 28 T-1-S, R-32-E NMFM  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Luck Morrow Lea New Mexico  
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is 3591 ft. RAB**DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

On 3-31-63 9-5/8" CD 40# J-55 ST&C casing was run and set at 4597' with a DV tool set at 2916. Cemented blow tool with 550 ex Incor 12% Gel and 1/2 lb/sx Flocele and 100 ex. Incor Neat. Cemented above DV tool with 3500 ex 12% gel Incor, cnt did not circulate. Filled to surface with 250 ex cnt, cnt circ. After WOC 18 hours, tested casing with 2000 PSI for 30 minutes before and after drilling plug. Test OK.

**Reduced hole to 8-1/2" at 4597' and resumed drilling operations.**

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum CorporationAddress Post Office Box 68Hobbs, New MexicoOriginal Signed by:  
Y. E. STALEY

By

Title Area Superintendent

10

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000