

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<p align="center"><b>SUNDRY NOTICES AND REPORTS ON WELLS</b></p> <p align="center"><small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small></p>		<p>5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/></p>
<p>6. Name of Operator <b>Gil-Mc Oil Corporation</b></p>		<p>5. State Oil &amp; Gas Lease No. <b>B-2657</b></p>
<p>7. Address of Operator <b>Box 763, Hobbs, New Mexico 88240</b></p>		<p>7. Unit Agreement Name</p>
<p>8. Location of Well UNIT LETTER <b>A</b> <b>660</b> FEET FROM THE <b>North</b> LINE AND <b>660</b> FEET FROM THE <b>East</b> LINE, SECTION <b>36</b> TOWNSHIP <b>18S</b> RANGE <b>36E</b> N.M.P.M.</p>		<p>8. Farm or Lease Name <b>State "A"</b></p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) <b>3757 DF</b></p>		<p>9. Well No. <b>1</b></p>
<p>12. County <b>Lee</b></p>		<p>10. Field and Pool, or Wildcat <b>Undes. (Eumont)</b></p>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <b>Re-enter</b> <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

**Drilled surface plug 10/13/78. Circulated out heavy mud to 2840. Drilled cement plug 2840 to 3200. Drilled plug at 4600. Circulated hole clean to 5212. Set bridge plug at 4900'. Treated with 500 gallons 15% super mud acid, flushed with 35 bbls 2% KCl water. Swabbed load. Run rods & tubing. Preparing to test.**

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John K. Ryan TITLE Agent DATE 1/16/79

APPROVED BY John K. Ryan TITLE Agent DATE JAN 17 1979

CONDITIONS OF APPROVAL, IF ANY: G