

(Revised 7/1/80)
(Form C-105)
N.

NEW MEXICO OIL CONSERVATION COMMISSION

WELL RECORD

A blank 10x10 grid for graphing, consisting of 10 columns and 10 rows of squares. The grid is used for plotting the graph of the function $y = \frac{1}{2}x^2$.

State "Ark"

AREA 640 ACRES
LOCATE WELL CORRECTLY

(Lease)

OIL SANDS OR ZONES

IMPORTANT WATER SANDS

CASING RECORD

MUDDING AND CEMENTING RECORD

RECORD OF PRODUCTION AND STIMULATION

...Depth Cleaned Out..... **11,785'**

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 11,833 feet, and from feet to feet.
Cable tools were used from 0 feet to 11,833 feet, and from feet to feet.

PRODUCTION

Devonian - Aug. 24, 1963

Put to Producing Abo 19

OIL WELL: The production during the first 24 hours was 304 barrels of liquid of which 100 % was
0 % was oil; 0 % was emulsion; 0 % water; and 0 % was sediment. A.P.I.
Devonian - 49.4°
Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian 11,608	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T. Bone Springs 8570	T. Morrison
T. Drinkard	T. Wolfcamp 9950	T. Penn.
T. Tubbs	T. Miss. Lime 10,930	T.
T. Abo 9010	T. Woodford 11,438	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	346	346	Surface				
346	1782	1436	Red bed & gyp				
1782	2018	236	Red bed, gyp, salt				
2018	2730	712	Anhy. & gyp				
2730	3060	330	Salt & anhy.				
3060	3550	490	Anhy.				
3550	7211	3661	Lime				
7211	7694	483	Lime & sand				
7694	7696	2	Sand				
7696	8346	650	Sand, lime				
8346	8477	131	Lime				
8477	8579	102	Sand, lime				
8579	8693	114	Sand, lime & chert				
8693	8853	160	Lime				
8853	8874	21	Lime & sand				
8874	8974	100	Lime				
8974	9432	458	Lime, shale				
9432	9834	402	Lime				
9834	9949	115	Lime & chert				
9949	10,257	308	Lime & sand				
10,257	11,000	743	Lime & shale				
11,000	11,451	451	Lime				
11,451	11,486	35	Lime & shale				
11,486	11,636	150	Shale				
11,636	11,833	197	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

October 28, 1963

(Date)

Company or Operator Tidewater Oil Company

Address Box 249, Hobbs, N. Mex.

Name Original Signed By

Position or Title

C. L. WADE

Area Supt.