Form 9-331 a (Feb. 1951)

X

Budget Bureau No. 42-R358.4. Form Approved.

| (SUBMIT IN TRIPLICATE)     | Land Office L.C.         |
|----------------------------|--------------------------|
| UNITED STATES              | Lease No. 063586         |
| DEPARTMENT OF THE INTERIOR | Unit So. Cal. Petr. Fed. |

## SUNDRY NOTICES AND REPORTS ON WELLS

GEOLOGICAL SURVEY 0 57

| NOTICE OF INTENTION TO DRILL<br>NOTICE OF INTENTION TO CHANGE PLANS<br>NOTICE OF INTENTION TO TEST WATER SHUT-OFF<br>NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL<br>NOTICE OF INTENTION TO SHOOT OR ACIDIZE<br>NOTICE OF INTENTION TO PULL OR ALTER CASING<br>NOTICE OF INTENTION TO ABANDON WELL | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
|--|--|
|  | ( NATURE OF REPORT, NOTICE, OR OTHER DATA) |

| Southern California Petro      | 1              |   | April 9                            | , 19 <b>63</b> |
|--------------------------------|----------------|---|------------------------------------|----------------|
| Well No is located             | <b>990</b> ft. | $from_{-} \left\{ \begin{matrix} N \\ N \\ M \end{matrix} \right\}$ line as | nd990 ft. from W line of sec.      | 29             |
| NW 29<br>(½ Sec. and Sec. No.) | 19.S<br>(Twp.) | <b>32 E</b><br>(Range)  | N. M. P. M.<br>(Meridian)          |                |
| Lusk Deep - Strawn<br>(Field)  | (Co            | Lea<br>unty or Subdivision)   | New Mexico<br>(State or Territory) |                |

The elevation of the derrick floor above sea level is 3554 ft. GL

## DETAILS OF WORK

| (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement<br>ing points, and all other important proposed work) |
|---|
|---|

4-1-63 T. D. 4497\*

Ran 142 jts. of 8-5/8" O. D. 32# J-55 casing set at 4497'. 2 stage tool at 2593'. Cemented first stage w/700 sacks pozmix & regular. Comented second stage w/2400 sacks pozmix, regular, gel 6% and salt saturated. Temp. Survey shows top at 2000'. Squeezed 1000 sacks salt saturated coment down outside of 8-5/8" O.D. casing, held 400 psig surface pressure. Test casing with 1000# for 30 minutes. Drilled plug after 24 hours W.O.C.

Address P. O. Box 1492

Bl Paso 99, Texas

Attention: Drilling Department

By \_\_

Title Supervising Petroleum Engineer