P. O. GOY 14:

Form Approved. Budget Bureau No. 42-R1424

HOBEL THE UNITED STATES

DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

5. LEASE NM35612

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

CHAIDDY	NOTICES	AND	DEDADTO	ON.	WELLO
SUNDKY	NUTICES	AND	REPORTS	UN	WHIIS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

	t t
1. oil gas other	
2. NAME OF OPERATOR	
Anadarko Petroleum Corporation	[,
3. ADDRESS OF OPERATOR	14
	• I

P.O. Box 806 Eunice, NM 88231 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & 660' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA

2	EADM	ΛĐ	LEAC	ENA	4 -

7. UNIT AGREEMENT NAME

Polewski Fed

9. WELL NO. 1

7					
10. £	ELD	\sim	14/11	DOAT	
10.4	ILLU	UK	WIL	.DCAT	NAME
	,				
ω					
<i>_</i>	7		_	-	

<u>Lusk-Delaware</u> 11. SEC., T., R., M., OR BLK. AND SURVEY OR

Sec 31,T 19S, R 32E 12. COUNTY OR PARISH 13. STATE Lea NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD) 3518.0

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Run 5½" csg cement

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - MIRUPU. TIH w/bit. CO mud & junk to 7163'. 1.
 - 2. RU Wireline & log from surface to TD 7163'.
 - Ran 7163' of $5\frac{1}{2}$ " 15.5# csg w/shoe set @ 7163', float collar set 3. @ 7123', and DV tool set @ 3003'.
 - 4. RU Western Co. & cemented 1st stage w/1050 SX of 50/50 Poz "C" cement. Plug down @ 3:45 P.M. 2-3-88. Opened DV tool & circ hole 4 hrs. Circ @ 90 SX to pit. Cemented 2nd stage w/400 SX Class "C" Lite cement & tailed in w/100 SX Class "C" Neat cement. Closed DV tool @ 8:15 P.M. 2-3-88. Circ 90 SX to pit.

Subsurface Safety Valve: Manu. and Ty							
18. I hereby certify that the foregoing is	true and corr	rect Field	Foreman	. DATE	February 4	, 1988	
	(This space	for Federal o	r State office use))		<u></u>	-
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	E		DATE			··

*See Instructions on Reverse Side