| X. | | | |
|----|------|------|---|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | ' |

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Menico

WELL RECORD 23 Fil 1 57

PBTD 9,180'

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission Submit in OUINTUIPINGATE.

If State Land submit 6 Copies

| | AREA 640 ACR | | of the Commi | ssion. Submit in | QUINTUPLICA | TE. It State | gand submit & Copies |
|----------------------------|-------------------|--|------------------------|--|------------------|---|---|
| TOCY. | LE METT COH | rectly | | 0. | . 4 6 . M | Vanita NATH | |
| TEXAC | O Inc. | (Company or Opera | lor) | St | ate of New | (Loase) | |
| Icli No | 9 | in NE | | 4, of Sec1 | 2 т | 18-S R | 34-E , NMP |
| Undesi | gnated V | acuum Abo I | Reef | Pool | Lea | | Coun |
| 7_11 | 990 | feet from | North | line and | 1980 | feet from | West i |
| C C | 12 | 16 20 | te Land the Oil an | d Gas Lesse No. | B-1258 | -1 | •••••• |
| | | | | | | | e 28 , 1963 |
| rilling Com | mencea | Marcui | n Drilling Co | ompany | 6 WE Complete | | |
| | | | | | | | ` |
| | | | | | | | o be kept confidential un |
| | | t Top of Tubing | | | Inc im | ormation given is t | o be kept confidencial un |
| | | | | | | | |
| See Att | ached | | - | L SANDS OR Z | | | |
| io. 1, from | ····· | | | | | | |
| o. 2, from | | to. | | No. 5 | , from | to | |
| lo. 3, from | ····· | to | | No. 6 | , from | to | |
| 50. 3, from 50. 4, from | WEIGH PER PC | T NEW O | R | CASING RECO | ` | feet. , | PURPOSE |
| 11-3/4" | 23.7 | | 3551 | Howco | None | None | Surface Intermediate |
| 8-5/8" 2-7/8" | 24.0 6.5 | | 9167' | Howco | None None | None See Attache | |
| 2 7,0 | 0,3 | o new | 310/ | 1 | | | |
| | | | | A 3270 CW3577377 | WALL DESCRIPTION | | |
| | | | | | TING RECORD | | AMOUNT OF |
| SIZE OF HOLE | BIZE OF CAEDIO | WHERE | NO. SACKS OF CEMENT | METHOD USED | O | MUD RAVITY | MUD USED |
| | 11-3/4" | 367' | 350 | Howco | | | |
| 10-5/8" 7-5/8" | | 3150' | 1650 1700 | Howco Howco | | | |
| 7-3/8 | 2-7/8" | 9179' | 1700 | HOWCO | | | |
| See Ati | tached | (Record th | RECORD OF I | | AND STIMULAT | | |
| | | | | | | **** | *************************************** |
| •••••• | • | | | | > | | |
| ••••••• | | ···· · · · · · · · · · · · · · · · · · | | ************************************** | | ••••••••••••••••••••••••••••••••••••••• | |
| •••••• | | | A.A 1 - 1 | ************************************** | ,, | ************************* | |
| Result of Pr | oduction Stin | ulationSee | Attached | ********************** | | *************************************** | *************************************** |
| | *********** | • | | ******************************* | | *************************************** | |
| | | | | | | Depth Cleaned | Out 10,192' |

COORD OF DRILLETTEM AND SPECIAL TECH

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

| | | | PRODU | OTION | | | |
|-----------------|--------------|----------------------|---|---|-----------|----------------------|--|
| Put to Pro | ducing | | July 10 , 19 63 | | | | |
| | | | during the first 24 hours was | 83 | barı | els of liou | aid of which 100 % w |
| OIL WEL | | | —— % was emulsion; | | | | |
| | | | | *************************************** | 70 Walti | , and | Was seament. The |
| | | • | 39.3 | | | | |
| GAS WEI | L: The | production | during the first 24 hours was | л | A.C.F. pl | 15 | barrels |
| | liqu | id Hydrocar | bon. Shut in Pressure | | | | |
| Length of | Time Sh | ut in | | • | | | |
| PLEA | SE IND | ICATE BE | LOW FORMATION TOPS (IN CON | FORMANO | E WITH | GEOGR | APHICAL SECTION OF STATE) |
| | | | Southeastern New Mexico | | | | Northwestern New Mexico |
| | | | T. Devonian | | | | Ojo Alamo Kirtland-Fruitland |
| | | 2810' | T. Silurian | | | Farmington | |
| | | | T. Simpson | | | | Pictured Cliffs |
| | | | T. McKee | | | | Menefee |
| | | | T. Ellenburger | | | | Point Lookout |
| | | | T. Gr Wash | | | | Dakota |
| | | | T. Cramer | | | | Morrison |
| | | | Т. | | | • | Penn |
| | | | T | | | | |
| | | | T | | | | |
| | | | Т | 1 | | | |
| | | | FORMATIO | ON RECO | RD | | |
| From | То | Thickness in Feet | Formation | From | То | Thickness in Feet | Formation |
| | 267 | | Caliche | | | | |
| 0 367 | 367 1655 | 367 1288 | Redbed | | | | : |
| 1655 | 1780 | 125 | Redbed & Anny | | | | : ! |
| 1780 2810 | 2810 | 1030 244 | Anhy & Salt Anhy & Gyp | | | | |
| 3054 | 4516 | 1462 | Anhy & Lime | | | | |
| 4516 5564 | 5564 5917 | 1048 353 | Lime & Sand Lime | | | | • |
| 5917 | 6807 | 890 | Lime & Dolomite | | | | • |
| 6807 7623 | 7623 7896 | 816 273 | Dolomite Lime & Chert | | | | |
| 7896 | 9306 | 1410 | Dolomite & Lime | | " | | |
| 9306 | 9810 | 504 | Sand, Lime & Dolomite | | | | |
| 9810 l Depth | 10192 | 382 | Lime & Sand | | | | |
| - | 9180 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| measure | ments | from ro | tary table or | 1 | | | |
| above g | | | - | | | | |
| | | | | | | | |
| | ' | 1 | ATTACH SEPARATE SHEET II | r ADDITIO | NAT. SP | ACE IS N | VEEDED |
| | | | | | | | |
| | | | that the information given herewith is ailable records. | a complete | and corre | ct record | of the well and all work done on it so |
| as can b | e uetermii | icu irom av | anaoic iccofqs, | | J. G. 1 | Blevins | , Jr. July 23, 1963 |
| | | | | | | | (Date) |
| Compan | v or Oher | ator) | TEXACÔ Inc. | Address | P.O. I | 30x728 | -Hobbs, New Mexico |