

Memo

From

JOE D. RAMEY
SUPERVISOR & PRORATION
MANAGER

J. Pennzoil

Huston #3

6605 + 1980E 9-18-38
TD 4753 5 1/2 on bottom
Perf 4717-22

Spot 15 3x3 over perf.

~~25~~ 25 3x3 stub

FF below salt

25 3x3 Base salt

25 " TOP "

25 " Base surface

10 3x3 CAP Verbo (9-25-63)

COUNTY	Lea		FIELD Bishop Canyon		STATE	N.M.		NO.
OPR.	Pennzoil Company							MAP
NO.	3 LSE. Huston							
SEC.	9	T. 18S	BLK. R	38E	SUR.	CO-ORD.		
LOC.	660' fr S Line & 1980' fr E Line of Sec.							
MI.	FROM		CLASS.		EL 36558			
SPUD.	8-30-63	COMP.	9-30-63	FORMATION	DATUM	FORMATION	DATUM	
TRT.				LOG:				
				SA	4656			
CSG. & SX	8 5/8"	367'	250					
	4 1/2"	4755'	280					
TBG.	DEPTH	SIZE						
LOGS	EL	GR	RA	IND	HC	A		
							TD	4755'
							PB	
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.	HRS. TEST
PLUGGED AND ABANDONED								

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Tom Brown Drlg. Co. PROP DEPTH 4900' TYPE
 DATE

9-6-63, PD 4900', San ANDres.
 Contractor - Tom Brown Drlg. Co.
 9-9-63 Drlg. 4582' dolo.
 9-16-63 TD 4755', WOC.
 DSI 4704-55', open 2 hrs,
 Rec. 1000' mud,
 30 min ISIP 1589#, FP 254-403#,
 60 min FSIP 1439#.
 9-23-63 TD 4755', swbg.
 Perf 4717-22' w/2 SPF,
 Ac 500 MA,
 Ac 2000 gals,
 Swbd dry,
 Frac 20,000 gals gelled (7 1/2%) acid + 18,000# sd.
 Swbd back load.

Lea Bishop Canyon N.M. Sec. 9-18S-38E
Pennzoil Company #3 Huston Page #2
9-30-63 TD 4755', prep to P&A.
Swbd 45 BW w/tr. oil in 12 hrs.
10-7-63 TD 4755', PLUGGED AND ABANDONED.