

WELL RECORD

AREA 640 ACRES  
LOCATE WELL CORRECTLY

STATE  
↓  
New Mexico "BV"

(COMPANY OR OPERATOR)

(LEASE)

WELL IS 510 FEET FROM North LINE AND 510 FEET FROM East LINE  
OF SECTION 18. IF STATE LAND THE OIL AND GAS LEASE NO. IS OG-4063

NAME OF DRILLING CONTRACTOR Rowan Drilling Company

ADDRESS \_\_\_\_\_ Midland, Texas

ELEVATION ABOVE SEA LEVEL AT TOP OF TUBING HEAD 3967 D.F.. THE INFORMATION GIVEN IS TO BE

KEPT CONFIDENTIAL UNTIL \_\_\_\_\_, 19\_\_\_\_ DATE WELL COMPLETED 10-10-63

DISTANCE FROM RDB TO CSG. HEAD FLANGE 20.12

## OIL SANDS OR ZONES

NO. 1, FROM DRY HOLE TO \_\_\_\_\_ NO. 4, FROM \_\_\_\_\_ TO \_\_\_\_\_

NO. 2, FROM \_\_\_\_\_ TO \_\_\_\_\_ NO. 5, FROM \_\_\_\_\_ TO \_\_\_\_\_

NO. 3, FROM \_\_\_\_\_ TO \_\_\_\_\_ NO. 6, FROM \_\_\_\_\_ TO \_\_\_\_\_

## IMPORTANT WATER SANDS

INCLUDE DATA ON RATE OF WATER INFLOW AND ELEVATION TO WHICH WATER ROSE IN HOLE.

NO. 1, FROM \* TO FEET.

NO. 2, FROM \_\_\_\_\_ TO \_\_\_\_\_ FEET.

NO. 3, FROM \_\_\_\_\_ TO \_\_\_\_\_ FEET. \_\_\_\_\_

NO. 4, FROM \_\_\_\_\_ TO \_\_\_\_\_ FEET. \_\_\_\_\_

## CASING RECORD

\* Crossed over to 10-3/4 two joints from surface

## MUDDING AND CEMENTING RECORD

TOP OF CEMENT.

## RECORD OF PRODUCTION AND STIMULATION

(RECORD THE PROCESS USED, NO. OF QTS. OR GALS. USED, INTERVAL TREATED OR SHOT.)

Acidized perf 11834-44 with 500 gals mud acid. Average injection rate 1.8 BPM. Max

Press 4200#. Min press 2000#. Job by Wilson Acidizing. Acidized perf 11834-44 with 2000

gals. reg 15% NE acid. Average injection rate 2.5 BPM, Max press 5000#. Min. press 3200#.

Spotted 1000 gals acetic acid on perf 11,833-38. Pumped 12 bbls acid into perf in 20 hrs.

RESULT OF PRODUCTION STIMULATION: Unsuccessful (Continued on Pa

(Continued on Page 3)

TOTAL DEPTH 11,883 (Driller's T.D.)

PBD Surface