

COUNTY	Lea	FIELD	Undesignated	STATE	N.M.	NO.
OPR.	Humble Oil & Refg. Company					MAP
NO.	1	LSE New Mexico-State "BV"				
SEC.	18	T.	18S	BLK.	35E	SUR.
LOC.	510' fr N & E Lines of Sec.					
MI.	FROM	P&A	CLASS.	EL 3967E		
SPUD.	6-12-63	COMP.	10-10-63	FORMATION	DATUM	FORMATION
IRT.				LOG:		
				Yates	3134	
CSG. & SX.				Queen	4240	
13 3/8"	310'	325		Penr	4470	
9 5/8"	3648'	850		SA	5090	
4 1/2"	11863'	1650		Glor	5780	
TBG.	DEPTH	SIZE		B Spg	6488	
LOGS	EL	GR	RA	IND	HC	A
				Wolfc	9282	
				TD	11883'	
						PB
PROD	INT.	(DAILY RATE)	BS&W	GH	GOR	GTY
						C. P.
						T. P.
						HRS. TEST
PLUGGED & ABAND ONED						
Distribution limited and publication prohibited by subscribers' agreement.						
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.						
CONT.	PROP DEPTH 11,900' TYPE					
DATE						

F.R. 6-6-63
PD 11,900' RT - Wolfcamp & Devonian

6-17-63 Drlg. 2028'.
6-24-63 Drlg. 4520'.
7-1-63 Drlg. 6896' lm.
7-8-63 Drlg. 7887' dolo.
DST (Bone Springs) 7220-7485', open 1 hr,
rec 840' DM + 4680' salt wtr,
1 hr ISIP 2947#, FP 2402-2947#,
2 hr FSIP 2947#.

7-15-63 Drlg. 8715' lm. & dolo.
7-22-63 TD 9886', fshg.
DST 8810-9000', open 1 hr,
rec 8' DM,
1 hr ISIP 130#, FP 130-130#,
1 hr FSIP 130#.
DST 9215-9290', open 1 hr 30 mins,
rec 275' DM, w/NS, 6460' SGC Salty Sul. Wtr,

-cont.-

7-22-63 -cont.-
1 hr ISIP 3260#, FP 611-3048#,
2 hr FSIP 3245#.
7-29-63 Drlg. 10032' dolo. & ch.
8-5-63 Drlg. 10809' lm. & sh.
DST 10085-177', open 1 hr 30 mins,
GTS 5 mins, @ est. 55 MCFGPD,
Rev out 350' oil, 182' sul. wtr CM + 2184'
salty sul. wtr
1 hr ISIP 3666#, FP 173-1086#,
1 hr FSIP 3451#.
8-12-63 Drlg. 11513' lm. & dolo.
8-19-63 TD 11863', prep to run casing.
DST (Devonian) 11836-863', open 2 hrs, used 1000'
WB, GTS 1 hr 35 mins @ TSTM,

Rev out WB + 858' oil & 90' DM,
1 hr ISIP 4682#, FP 523-854#,
2 hr FSIP 4678#.
8-26-63 TD 11863', prep to drill out.
Perf 11834-844' W/2 SPF, Ac. 500 gals
Swbd 70 BO + 2 BAW in 8 hrs.
Re-Ac. 2000 gals, swbd 10 BO + 90 BNW/9 hrs.
Set ret. @ 11796' & squeezed perfs 11834-844'
W/100 sx. Re-squeezed with 75 sx.
9-9-63 TD 11863', PB 11850', prep to test.
Re-Perf 11833-838' W/1 SPF, Ac. 1000 gals.
9-16-63 TD 11863', PB 11850', prep to squeeze.
Swbd 56 BW/9 hrs.
9-23-63 TD 11863', PB 11850', swbg.
Squeezed perfs 11833-838' W/100 sx.
Re-Perf 11833-838' W/1 SPF, Ac. 1000 gals,
Swbd 70 BW/10 hrs, with tr. of oil.

Lea Undesignated N.M. Page 3
Humble Oil & Refg. Co., #1 New Mexico-State "BV" - Sec.
18-18S-35E

9-30-63 TD 11863', milling @ 11862'.
Swbd 64 BW + tr. oil in 10 hrs.
Squeezed perfs 11833-838' W/50 sx.
10-7-63 TD 11883', prep to Temp. Abd.
Ac. Open Hole 11863-883' W/500 gals
Swbd 90 BW/10 hrs.
10-14-63 TD 11883', PLUGGED & ABANDONED
LOG TOPS: Cisco 10231?, Canyon 10504', Strawn
10682', Morrow 10800', Mississippian Lime 11098',
Woodford 11678', Devonian 11831'.