



(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYJ. L. GORDON
ACTING DISTRICT ENGINEER

Land Office

Lease No.

LC-063586

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Dallas, Texas December 5, 1963

Well No. 3 is located 1280 ft. from {N} line and 1280 ft. from {E} line of sec. 29

SW/4 Sec. 29

(1/4 Sec. and Sec. No.)

T-19-S

(Twp.)

R-32-E

(Range)

N.M.P.M.

(Meridian)

Lusk Strawn

(Field)

Lee

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3361 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

4600' of 8 5/8" 32# J-55 casing was cemented at 4308' as follows: A D.V. Packer tool was placed in the string at 2744'. The first stage out the shoe was 500 sacks of incore plus 82 gal followed by 150 sacks of neat cement. Then circulation above 2744' was established and cemented by 1000 sacks incore plus 6% gel plus 100 sacks neat.

After the D.V. tool was drilled out, a pressure of 1500 PSI was applied at the surface for 30 min. There was no pressure drop.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Southern New Mexico Oil Corp.

Address 3108 Southland Center

Dallas 1, Texas

By

G. L. Hall

Title

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. **LC-063586**

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Dallas, Texas December 3, 1963

Well No. **3** is located **1980** ft. from **N** line and **1980** ft. from **E** line of sec. **29**

SW/4 Sec. 29

(1/4 Sec. and Sec. No.)

T-19-S

(Twp.)

R-32-E

(Range)

N.M.P.M.

(Meridian)

Lusk Strawn

(Field)

Lea

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is **3561.3** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The above well was spudded at midnight October 25, 1963. 800' of new 13 3/8" 48# H-40 casing was circulated by cement at 788' on October 27th. After 24 hours a pressure of 1000 PSI was applied at the surface for 30 min. There was no pressure loss.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Southern New Mexico Oil Corp.**Address **3108 Southland Center****Dallas 1, Texas**By **P. L. Hall**Title **V.P.**