

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. K-2527	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator H. L. Brown, Jr.		8. Field or Lease Name Huston
3. Address of Operator 309 Midland Tower, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>9</u> TOWNSHIP <u>18 S</u> RANGE <u>38E</u> NMPM.		10. Field and Pool, or Wildcat Bishop Canyon San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3653' GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

WELL DATA

10-3/4" casing set at 356' with 300 sxs cement
7-5/8" casing set at 4884' with 300 sxs cement
Perforated at 4757' with 4 shots
TD 8245'.
Bridge plug set at 4850'.

PROPOSED PLUGGING PROCEDURE

Set cast iron bridge plug at 4740' with 10' cement on top.
Loaded hole with mud laden fluid.
Set 10 sx plug in surface with dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED B. D. Baker TITLE Petroleum Engineer DATE October 2, 1970

APPROVED BY John W. Runyan TITLE Engineer DATE OCT 5 1970
CONDITIONS OF APPROVAL, IF ANY: