Form 9-881 a (Feb. 1961)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY 1903 AUG 12 III 8 39

| Form Approved, | | | | | | | | |
|----------------|---|------------------------------|-------------------|----|-----------|----|---|--|
| Land Office | • | 6,2 9 3,77 3,77 | | | - | | | |
| Lease No. | | |) em | | | | | |
| Unit | | | \mathcal{L}_{s} | 2. | • | ". | , | |

Budget Bureau No. 42-R358.4.

| SUNDRY | NOTICES | AND | REPORTS | ON | WELL |
|--------|----------------|-----|----------------|----|------|

| | 78162 |
|--|---|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR. |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO PULL OR ALI'ER CASING | SUPPLEMENTARY WELL HISTORY |
| NOTICE OF INTENTION TO ABANDON WELL. | |
| | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

| Buffalo Federal Unit | • | July 25, | , 19 <u>_53</u> |
|-------------------------|-------------------------|--------------------|-----------------|
| Well No. 6 is located | 660 ft. from (S) line | | of sec. 33 |
| SW/4, SE/4, Sec. 33 | T-18-S R-33-E | NMPM | |
| (1/4 Sec. and Sec. No.) | (Twp.) (Range) | (Meridian) | |
| Wildcat | Loa | oolxeM weW | • |
| (Field) | (County or Subdivision) | (State or Territor | y) |

The elevation of the derrick floor above sea level is MYA ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Cactus Drilling Company spudded 17-1/2" hole at 12 Noon on 7-23-63. On 7-24-63, 13-3/8" OD 35.6% SJ casing was run and set at 322' with 320 sx. cement. Cement circulated. After WOC 18 hours, tested casing with 600 PSI for 30 minutes. Test 0.K. Reduced hole to 11" at 322' and resumed drilling operations. Contractor proposes to set an 8-5/8" cave string at approximately 1600' and use cable tools to 3rill an 8" hole below to total depth.

| | ed that this plan of work must receive approval in writing by Pan American Petroleum Corporat | the Geological Survey before operations may be commenced. |
|-------------------|---|---|
| Address | Post Office Box 68 | Original Signed by: D. R. MOONHEAT |
| Hobbs, New Mexico | | Ву |
| ************* | | Title Area Clerk |

(Marie

√. **3°** (2° ±

7 11

40.

ATM

of 1809 to many appended 19-1/27 hole at 18 10 to 10 t

Par arrices Tetro seus Corporation

10.0 000 0000 000 58

tained seed parties