

MN 20503

COUNTY LEA FIELD Vacuum STATE NM OWWO

OPR TEXACO INC. MAP

7 New Mexico "R" State

Sec 6, T-18-S, R-35-E CO-ORD

2310' FNL, 1650' FEL of Sec

		CLASS		OWOF EL 3983' E	
Re-Cmp 7-28-71		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
11 3/4" at 360' w/400 sx					
8 5/8" at 3032' w/1650 sx					
2 7/8" at 8847' w/1550 sx					
LOGS EL GR RA IND HC A					
		TD 8850'; PBD 8525'			

(Abo) Perfs 8384-8510' NO NEW POTENTIAL

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 8510' TYPE WO


8-9-71 F.R.C. 8-12-71; Opr's Elev. 3983' DF
PD 8510' WO (Abo)
(Orig. comp. 7-29-63 thru (Abo) Perfs 8533-8689',
OTD 8850', OPB 8816')
TD 8850'; PBD 8525'; COMPLETE
Sqzd Perfs (8533-8689') w/100 sx
Perf @ 8384', 8392', 8399', 8410', 8420', 8427',
8436', 8446', 8470', 8479', 8488', 8490', 8499',
8501', 8508', 8510' w/1 SPI
Acid (8384-8510') 10,500 gals (20% NEA)

8-12-71 COMPLETION REPORTED

COUNTY	Lea	FIELD	Vacuum-Abo	STATE	N.M.	NO.
OPR.	Texaco Inc.	MAP				
NO.	7	LSE	State of New Mexico "R" (NCT-1)			
SEC.	6	T.	18S	BLK.	35E	SUR.
LOG.	2310'	fr	N Line & 1650'	fr	E Line of Sec.	
MI.		FROM		CLASS.		EL 3983
SPUD.	6-24-63	COMP.	7-29-63	FORMATION	DATUM	FORMATION DATUM
TBT.	9000 gals acid	LOG:				
		Yates 2816				
CSG. & SX.		Queen 3743				
	11 3/4" 360' 400	SA 4380				
	8 5/8" 3032' 1650	Glor 6080				
	2 7/8" 8847' 1550	Abo 8065				
TBG.	DEPTH	SIZE	Abo Rf			
LOGS	EL GR RA IND HC A	8452				
		TD	8850'	PB 8816'		
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.
8533-8689'	Flo. 197 BO	20/64"	920	38.1	200#	24'
(Abo)						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 8850' TYPE


 8-5-63

F.R. 6-13-63, Abo.
 PD 8850'
 7-1-63 Drlg. 3364' ls.
 7-8-63 Drlg. 5720' dolo. & sd.
 DST 5000-5110', open 1 hr, rec 540' MC Sul. Wtr,
 30" ISIP 1295#, FP 145-300#, 60" FSIP 1238#.
 7-15-63 Drlg. 7305' ls. & sd.
 DST 5949-5975', open 1 hr 30 mins, rec 90' MC
 Sul. Wtr + 320' sul. wtr, ISIP 2196#, FP 121-263#,
 FSIP 2196#.
 7-22-63 TD 8850' ls., prep to run casing.
 7-29-63 TD 8850' ls., PB 8816', tstg.
 Perf 2/8533-35', 2/8545-47', 2/8573-75', 2/8592-
 94', 2/8612-14', 2/8646-48', 2/8657-59', 2/8676-
 78', 2/8687-89', treated 9000 gals acid.
 Swbd & fld. 221 BL&AW/31 hrs.
 8-5-63 TD 8850' ls., PB 8816', COMPLETED.

