

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. <b>K-2527</b>		

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>H. L. Brown, Jr.</b>	8. Farm or Lease Name <b>Huston</b>
3. Address of Operator <b>309 Midland Tower, Midland, Texas 79701</b>	9. Well No. <b>2</b>
4. Location of Well UNIT LETTER <b>G</b> <b>1980</b> FEET FROM THE <b>North</b> LINE AND <b>1980</b> FEET FROM THE <b>East</b> LINE, SECTION <b>9</b> TOWNSHIP <b>18S</b> RANGE <b>38 E</b> NMPM.	10. Field and Pool, or Wildcat <b>Bishop Canyon San Andres</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3656' GL</b>	12. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

### WELL DATA

8-5/8" casing set at 336' with 160 sxs cement  
5-1/2" casing set at 4743' with 275 sxs cement  
TD 4743'  
Perforated at 4712' & 4717'

### PROPOSED PLUGGING PROCEDURE

Set cast iron bridge plug at 4700' with 10' cement on top  
Load hole with mud laden fluid  
Set 10 sx plug in surface with dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED B. D. Baker B. D. Baker TITLE Petroleum Engineer DATE October 2, 1970

APPROVED BY John W. Runyan TITLE Engineer DATE OCT 5 1970

CONDITIONS OF APPROVAL, IF ANY: