

COUNTY	Lea	FIELD	Bishop Canyon	STATE	N.M.	NO.
OPR.	Pennzoil Company					MAP
NO.	2	LSE	Huston	BLK.		
SEC.	9	T.	18S	R.	38E	SUR.
LOC.	1980' fr N & E Lines of Sec.					
MI.	FROM		CLASS.		EL. 36598	
SPUD.	6-17-63	COMP.	7-17-63	FORMATION	DATUM	FORMATION
TRT.	9000 Ac., AF 15,000			LOG:		
	+ 7500# sd.			Anhy	1860	
CSG. & SX.				Yates	2805	
	8 5/8"	346'	160	7-R	3210	
	5 1/2"	4743'	225	Queen	3810	
				Gryb	4205	
TBG.	DEPTH	SIZE		SA	4644	
LOGS	EL	GR	RA	IND	HC	A
				TD	4743'	PB 4729'
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.
4712-17'	Pump 54 BO + 27 BW				35.9	24'
(San Andres)						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Co. Tools	PROP DEPTH 4800'	TYPE
DATE		

6-24-63 F.R. 6-6-63, San Andres PD 4800'-Co. Tools
Dilg. 4135' ls. & sd.
7-1-63 TD 4743', prep to perf.
DST 4695-4723', open 4 hrs, GTS 2 hrs & 12 mins,
rec 335' oil, 95' wtr, 30" ISIP 1320#, FP 65-335#,
30" FSIP 1170#.
7-8-63 TD 4743', swbg.
Perf @ 4712' & 4717', treated 1000 gals acid.
7-15-63 TD 4743', SI.
Swbd dry.
7-22-63 TD 4743', PB 4729', COMPLETED.
Re-Perf @ 4712' & 4717', treated 8000 gals acid,
AF 15,000 gals gelled acid + 7500# sd.
(Holding for amended operator).
7-25-63 AMENDED OPERATOR: was Tom Brown Drlg. Co., Inc.
8-1-63 TD 4743', PB 4729', COMPLETION REPORTED.