SUPPLEMENTAL WELL INFORMATION

NAME OF WELL AND NUMBER	New Mexico State "BC" #8	•
POOL COMPLETED IN	Vacuum Abo	 •
PERFORATED INTERVAL 8453	8,8460,8472,8480,8507,8517,8526,8545,8557,8575,8592, 8,8616,8636,8658,8670 one shot per depth by Lane Wells.	— ·
STIMULATIONS:		

See front page.

POTENTIAL TEST

· ·				1	GAS		TBG PR	CSG PR	
HOKE	HOURS	BBLS/	/DAY	% OF	MCF		OR	OR	CORRECTED
IZE	TESTED	FLUID	OIL	BS&W	/DAY	GOR	S P M	L. STROKE	GRAVITY
6/64	7-1/4	440	337	12	340	880	390	Packer	39.50
I	ZE	ZE TESTED	ZE TESTED FLUID	ZE TESTED FLUID OIL	ZE TESTED FLUID OIL BS&W	OKE HOURS BBLS/DAY % OF MCF ZE TESTED FLUID OIL BS&W /DAY	OKE HOURS BBLS/DAY % OF MCF ZE TESTED FLUID OIL BS&W /DAY GOR	OKE HOURS BBLS/DAY % OF MCF OR ZE TESTED FLUID OIL BS&W /DAY GOR S P M	OKE HOURS BBLS/DAY % OF MCF OR OR ZE TESTED FLUID OIL BS&W /DAY GOR S P M L. STROKE

DRILL STEM TESTS PRESSURES INTERVAL TESTED RUN BY RECOVERY - FEET TO F. FLOW. FROM RESERVOIR NO. Cook 220' of GCDM and 2888 7802 7725 260' of 0 & GCM

CORES: None

LOGS: Gamma Ray-Sonic-Welex-from 9025 to surface on 5-17-63. Frac Finder-Welex-from 9025 to 7000 on 5-17-63. Forxo with caliper-Welex-from 9025 to 7000 on 5-17-63. Guard with S.P.-Welex-from 9025 to 7000 on 5-17-63.

UNSUCCESSFUL COMPLETION ATTEMPTS: FROM None TO (SEE DAILY DRILLERS REPORTS FOR SQUEEZES OR BRIDGES.)