



Lateral: 0

Proposed Direction: 99.8

Dog Leg Severity per: 100 feet

Measured Depth	Inclination	Azimuth	True Vertical Depth	North/South Coordinate	East/West Coordinate	Vertical Section	Dog Leg Severity	Survey Tool
5903	1.20	347.30	5902.40	11.40	-9.20	-11.01	0.00	
5945	18.70	115.80	5943.68	8.87	-3.18	-4.64	46.35	
5955	24.20	116.10	5952.99	7.27	0.11	-1.13	55.01	
5965	30.00	117.20	5961.89	5.23	4.18	3.23	58.21	
5975	36.70	116.00	5970.24	2.77	9.09	8.49	67.32	
5985	43.80	113.20	5977.86	0.10	14.97	14.73	73.25	
5995	50.70	110.50	5984.65	-2.63	21.78	21.91	71.78	
6008	59.70	107.30	5992.06	-6.06	31.87	32.44	72.11	
6039	80.00	101.40	6002.69	-13.14	59.93	61.29	67.84	
6068	85.60	100.10	6006.33	-18.50	88.18	90.05	19.82	
6100	88.00	100.10	6008.11	-24.11	119.64	121.99	7.50	
6131	87.90	99.40	6009.22	-29.35	150.17	152.97	2.28	
6162	88.30	100.10	6010.25	-34.60	180.70	183.96	2.60	
6194	87.90	100.70	6011.31	-40.37	212.16	215.94	2.25	
6225	87.70	101.10	6012.50	-46.23	242.58	246.91	1.44	
6256	88.80	101.20	6013.45	-52.22	272.98	277.88	3.56	
6287	88.40	102.80	6014.20	-58.67	303.29	308.85	5.32	
6319	88.10	102.30	6015.18	-65.62	334.51	340.80	1.82	
6349	88.20	102.20	6016.15	-71.98	363.81	370.76	0.47	
6380	87.80	102.50	6017.23	-78.60	394.08	401.71	1.61	
6412	88.50	102.40	6018.26	-85.50	425.31	433.66	2.21	
6443	89.00	102.00	6018.94	-92.05	455.60	464.62	2.07	
6474	88.10	101.10	6019.73	-98.25	485.96	495.60	4.11	
6507	88.10	101.10	6020.82	-104.60	518.33	528.57	0.00	

SUR: 330/N + 560/W
 BAL: 435/N + 1078/W
 D-6-185-350
 30-025-20753