

Form 10-68
(May 1968)

UNITED STATES
DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

COPY TO O. C. G.

Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-01135

6. IF INDIAN, ALLOTTED OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to complete or plug back an oil or gas reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any applicable regulations.
See also space 17 below.)
At surface

U. S. GEOLOGICAL SURVEY

HOBBS, NEW MEXICO

660' FN L x 760' FWL Sec 3 (UNIT D, NW 1/4 NW 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3569' RDB

7. UNIT AGREEMENT NAME

PLAINS UNIT FED

8. FARM OR LEASE NAME

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

WILDCAT - DELAWARE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

33-19-32 NMPM

12. COUNTY OR PARISH

LEA

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In accordance w/ Form 9-331 dated 11-11-68, abandoned Bone Springs and recompleted in the Delaware as follows: Spotted 40' cement plug 7599-7275 and covered Bone Springs perfsl 7535-7545). Did not out casing. Perforated 5740-43 w/ 4 SPF and cemented behind 5" w/ 300 ex neat. Perforated 4840-60 w/ 2.5 SPF. Acidized w/ 500 gal MCA. Evaluated! Dry. CIBP set @ 4797'. Squeezed 4840-60 w/ 100 ex cement. Perforated 4712-32' w/ 2.5 SPF. Acid w/ 500 gal MCA. Fraced w/ 5000 gal oil + 5000 # Sand. Evaluated:
PT. Swab & Flow 105 BO x 6 BW 12 hours.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AREA SUPERINTENDENT

DATE

DEC 30 1968

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

JAN 2 1969

J L GORDON
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

0+4- USGS-11
1- NSW
1- SUSP
1- R2Y
1- MOBIL