

CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.

B-10784

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
AMOCO PRODUCTION COMPANY	State "CT"
3. Address of Operator	9. Well No.
P. O. BOX 68 HOBBS, NEW MEXICO 88240	1
4. Location of well	10. Field and Pool, or Wildcat
UNIT LETTER <u>P</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>3</u> TOWNSHIP <u>18-S</u> RANGE <u>34-E</u> NMPM.	Vacuum GSA
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4019' GR	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	
		OTHER ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug and abandon the subject well as follows:
MISU and POH w/ rods, pump, and tubing. RIH w/ CIB and set at 4400'. Cap with 35' Class C heat cement. *Spot between all plugs w/ 10# brine with 25# gel/BBK. Pull up and spot a 100' class C heat cement plug across 3430-3330' (8 7/8" csg shoe 3381'). Spot 100' class C heat from 3150'-3050' (TCMT in 4 1/2" csg @ 3100' via bond log). Perforate 2350' w/ 4 DRTSPF. RIH and set cement retainer at 2250'. Squeeze perfs with 35SX class C heat cement. String out of retainer and dump excess cement. Perforate 350' w/ 40 DJS PF. Establish circulation on both 13 3/8"-8 7/8" and 8 7/8"-4 1/2" casing annulus. Pump 100 SX of class C heat cement and circulate both Annuli. Shut valve x Squeeze cement. Leave cement surface in 4 1/2" csg. Cap well erect 1x marker. MISU

O+5 NMOC-D-H 1-JRB 10-FJN 1-CMH

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

TITLE ADMINISTRATIVE ANALYST (SG)

DATE 12/31/85

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE JAN 2 - 1986

RECEIVED

DEC 31 1985

MODERN OFFICE