

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instruction
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ Drilling Well		5. LEASE DESIGNATION AND SERIAL NO. LC-065863
2. NAME OF OPERATOR Southern New Mexico Oil Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 1659, Midland, Texas		7. UNIT AGREEMENT NAME Lusk Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1650' from South Line & 970' from West line of Sec. 20		8. FARM OR LEASE NAME
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3567.7 Gr.	9. WELL NO. 7
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		10. FIELD AND POOL, OR WILDCAT Lusk Unit
NOTICE OF INTENTION TO:		11. SEC., T., S., M., OR BLK. AND SURVEY OR AREA NW/4 of SW/4 Sec. 20, T-1N-S, R-32-E
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	12. COUNTY OR PARISH
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	13. STATE New Mexico
SHOOT OR ACIDIZE ☐	ABANDON* ☐	
REPAIR WELL ☐	CHANGE PLANS ☐	
(Other) ☐		
		SUBSEQUENT REPORT OF:
		WATER SHUT-OFF ☒
		REPAIRING WELL ☐
		FRACTURE TREATMENT ☐
		ALTERING CASING ☐
		SHOOTING OR ACIDIZING ☐
		ABANDONMENT* ☐
		(Other) ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On Feb. 19, 3760' of new 8 5/8" 32# J-55 casing was cemented at 3796' as follows:

600 sacks were pumped out the shoe at 3796' when the tool (set at 2367') was open and circulation established - about 200 sacks excess cement was circulated out. On the second stage 1750 sacks were pumped out at 2387' through a D.V. tool. About 100 sacks excess cement was circulated. Last plug down at 1:30 AM. After 24 hrs. a pressure of 2000 psi was applied at the surface for 30 min. There was no pressure drop.

18. I hereby certify that the foregoing is true and correct

SIGNED E. H. Secor TITLE Agent DATE 2/21/64

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

FEB 24 1964

*See Instructions on Reverse Side J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.