

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIP  
(Other instruction  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME Lusk Deep Unit
2. NAME OF OPERATOR El Paso Products Company	8. FARM OR LEASE NAME Lusk Deep
3. ADDRESS OF OPERATOR c/o Hobbs Pipe & Supply Co., Box 2010 Hobbs, N.M.	9. WELL NO. 9
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface  660' FNL & 990' FWL	10. FIELD AND POOL, OR WILDCAT Lusk Drawn
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) UK
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 17 - 19S - 32E
	12. COUNTY OR PARISH Lea
	13. STATE N.M.

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 1 - Spotted a 25 sk cement plug to cover perfs. from 11364' to 11428'
- 2 - Spotted a 25 sk cement plug to cover perfs. from 8794' to 8799'
- 3 - Spotted a 25 sk cement plug at stub of 4 1/2" csg. @ 7200'
- 4 - Spotted a 35 sk cement plug at base of 8 5/8" csg. @ 3760'
- 5 - Spotted a 25 sk cement plug @ 2500' - 2600'
- 6 - Spotted a 25 sk cement plug @ 700' - 800'
- 7 - Spotted a 10 sk cement plug at top
- 8 - Hole was loaded w/mud-laden fluids and a 4" reg. marker erected.
- 9 - Well was Plugged and Abandoned 10/2/71

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

10/12/71

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

\*See Instructions on Reverse Side