

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. <u>NM 136-120</u>
2. NAME OF OPERATOR <u>El Paso Products Company</u>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <u>c/o Hobbs Pipe & Supply Company, Box 2010, Hobbs, N.M.</u>		7. UNIT AGREEMENT NAME <u>Lusk Deep Unit</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) <u>At surface</u> <u>660' FNL & 990 FWL</u>		8. FARM OR LEASE NAME <u>Lusk Deep</u>
14. PERMIT NO.		9. WELL NO. <u>9</u>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <u>UK</u>		10. FIELD AND POOL, OR WILDCAT
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>17 - 19S - 32E</u>
		12. COUNTY OR PARISH <u>Lea</u>
		13. STATE <u>N. M.</u>

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☒ XX
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposed Plugging Procedures:

1. Spot a 25 sx cement plug to cover perforations from 11,364' to 11,428'.
2. Spot a 25 sx cement plug to cover perforations from 8,794' to 8,799'.
3. Spot a 25 sx cement plug at stub of 4-1/2 casing.
4. Spot a 35 sx cement plug at base of 8-5/8" casing - (3760').
5. Spot a 25 sx cement plug at 2500' - 2600'.
6. Spot a 25 sx cement plug at 700' - 800'.
7. Spot a 10 sx cement plug at top.
8. Hole will be loaded with mud-laden fluids and a 4" regular marker erected.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

9/16/71

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

DATE

CONDITIONS OF APPROVAL, IF ANY:

SEP 1 1971

*See Instructions on Reverse Side

J L GORDON

RECEIVED

SEP 21 1971

OIL CONSERVATION COM. M.
HOBBES, N. M.