

COUNTY	LEA	FIELD	Lusk	OWWO
OPR	EL PASO PRODUCTS CO.		STATE	NM MN 20875
	9 Lusk Deep Unit		MAP	
	Sec 17, T-19-S, R-32-E			
	660' FNL, 990' FWL of Sec		CO-ORD	
	Re-Spd 5-20-71			
	Re-Cmp 5-24-71		CLASS	OWDF EL 36208
CSG & SX - TUBING	FORMATION	DATUM	FORMATION	DATUM
13 3/8" at 840' w/775 sx				
8 5/8" at 3780' w/1750 sx				
4 1/2" at 11,510' w/600 sx				
LOGS EL GR RA IND HC A				
	TD 11,510'; PBD 8938'			
TEMPORARILY ABANDONED				

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Logging Service, Inc.

CONT.	PROP DEPTH	8799'	TYPE	WO
DATE				

6-7-71

6-10-71

F.R.C. 6-10-71; Opr's Elev. 3620' DF
 PD 8799' WO (Bone Spring)
 (Orig. Southern New Mexico Oil Corp., comp
 7-25-64 thru (Strawn) Perfs 11,364-428',
 OTD 11,510', OPB 11,485')
 TD 11,510'; PBD 8938'; TEMPORARILY ABANDONED
 BP @ 8938'
 Perf 8794-99' w/2 SPF
 Acid (8794-99') 500 gals (20% HCL)
 Swbd 33 BHOCAW (8794-99')
 Swbd dry (8794-99')
 COMPLETION REPORTED

COUNTY	LEA	FIELD	Lusk-Strawn	STATE	N.M.
OPR	SOUTHERN NEW MEXICO OIL CORPORATION				JAP
9 Lusk Deep Unit-Federal					
Sec. 17, T-19-S, R-32-E				CO-ORD	
660' fr N Line & 990' fr W Line of Sec.					
Spud 6-8-64					
Comp 7-25-64		CLASS EL 36208			
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
13 3/8"	840'	775	Anhy	829	
8 5/8"	3780'	1750	Yates	2644	
4 1/2"	11510'	600	7-R	2980	
			Gryb	3616	
			SA	3997	
LOGS EL GR RA IND HC A			Del	4624	
TD 11510', PBD 11485'					

IP Strawn Perfs 11364-428' Flwd 424 BOPD. Pot. Based on 6 hr test of 106 BO thru 15/64" chk., TP 600#, CP 1700#, gravity 46.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 11,500' TYPE
DATE

F.R. 6-11-64; Oper's Elev. 3632' KB
PD 11,500' - Strawn
6-15-64 TD 3780', running 8 5/8" casing.
6-22-64 Drlg. 5300' 1m.
6-29-64 Drlg. 8088' 1m.
7-6-64 Drlg. 9863' 1m.
7-13-64 TD 11510', prep to log.
7-20-64 TD 11510', PBD 11485', flowing to clean.
Perf 11364-368', 11382-384', 11408-428' W/2 SPF
Ac. 1000 gals (MA)
7-27-64 TD 11510', PBD 11485', WO Potential.
Flwd 252 BO in 24 hrs thru 15/64" chk., TP 850#, CP 1750#.
8-3-64 TD 11510', PBD 11485', COMPLETED.
LOG TOPS: Bone Spring 7023', Wolfcamp 10396',
Strawn 11248'.