| Form 9-331 (May 1963) | UNITED STATES | SUBMIT IN TRIELICATE. | | |
|---|--|-------------------------------------|---|--|
| | DEPARTMENT OF THE INTER | IOR (Other Instructions on re- | 5. LEASE DESIGNATION AND SERIAL NO. | |
| | GEOLOGICAL SURVEY | | LC068019 | |
| SUN | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | | | |
| (Do not use this | | | | |
| OIL GAS WELL | 7. UNIT AGREEMENT NAME - Lusk Deep Unit | | | |
| 2. NAME OF OPERATOR | 8. FARM OR LEASE NAME | | | |
| El Paso | Lusk Deep | | | |
| 3. ADDRESS OF OPERATO | 9. WELL NO. | | | |
| c/o Hobbs Pi | 10 | | | |
| 4. LOCATION OF WELL (See also space 17 be At surface | 10. FIELD AND POOL, OR WILDCAT | | | |
| 1650' FNL & 1678' FWL | | | 11, and, T, R, M, OR HEM, AND SUMVRY OR ALEA- | |
| | | | 19 - 19S - 32E | |
| 14. PERMIT NO. 16. ELEVATIONS (Show whether DF, ST, CR, etc.) | | P, BT, GR, etc.) | 12. COUNTY OR PARISH 13. STATE | |
| | UK | | Lea N. M. | |
| 16. | Check Appropriate Box To Indicate I | Nature of Notice, Report, or (| · · · · · · · · · · · · · · · · · · · | |
| | UENT REPORT OF: | | | |
| TEST WATER SHUT- | PULL OR ALTER CASING | WATER SHUT-OFF | REPAIRING WELL | |
| FRACTURE TREAT | MULTIPLE COMPLETE | FRACTURE THEATMENT | ALTERING CASING | |
| SHOOT OR ACIDIZE | ABANDON* X | SHOOTING OR ACIDIZING | ABANDONMENT* | |
| REPAIR WELL | CHANGE PLANS | (Other) | | |
| (Other) | | (Norg: Report results | Nork: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) | |
| 17. DESCRIBE PROPOSED (proposed work. I nent to this work.) | OR COMPLETED OPERATIONS (Clearly state all pertine if well is directionally drilled, give subsurface loc | of defails and give portinent deter | including estimated data of starting and | |

Proposed Plugging Procedures:

- 1. Spot a 25 sx cement plug to cover existing perforations.
- 2. Spot a 25 sx cement plug at stub of 4-1/2 casing.
- 3. Spot a 35 sx cement plug at base of 8-5/8 casing (3760')
 4. Spot a 25 sx cement plug at 2300' 2400'.
- 5. Spot a 25 sx cement plug at 700' 800'.
- 6. Spot a 10 sx cement plug at top.
- 7. Hole will be loaded with mud-laden fluids and a 4" regular marker erected.

| | · | | |
|--|-------|-------|--------------|
| 18. I hereby certify that the toregoing is true and co | TITLE | Agent | DATE 9/16/71 |
| (This space for Federal or State office use) | | | |
| APPROVED BY | TITLE | APPRO | OVEDDATE |

RECEIVED

SEP 2 11971 OIL CONSERVATION COLAL MODES, EL EL