
ONE COPY OF BE FILED WITH EACH COMPLETIC REPORT

Field Name Undesign	nated (VecumeGloria	eta) County	Lea	OCC No. I
Standard O	1 Company of Texas	, A		
Operator Division of	California Oil Co.	Address	Drawer "S"	City Monahana, Texas
lease Name & No.	Vac Edge Unit	Well No.	2-G	Section 5, T-18
, cont. Traine to 110	(B-2073)			
		ECORD OF INCL	INATION	2.1.
Depth (feet)	Angle o	of Legrees) Di	splacement (feet)	Accumulative Displacement (feet)
<u>350</u>	1/4		1.53	1.53
850	1/4	 	2.18	3.71
1600	1/4		3.27	6 .98
2100			8.73	<u></u>
<u>2600</u> 2912	1-1/2		13.09 1.36	<u>28.80</u> 30.16
3280	1		6.42	36.58
3600	1/4		1.40	37.98
3990	3/4		5.10	43.08
<u>4111</u> 4296	1		<u>2.11</u> .81	45.19 46.00
4910	- 1/4		2.68	48.68
5300	1-3/4	·	11.91	60.59
5460	1		2.79	63.38
5500 5932	1-1/4		<u>.87</u> 3.77	<u>64.25</u> 68.02
6262 T.D.	1		5.76	73.78
				
Was survey run in To Distance to nearest Distance to lease 1:	lease line 330 ines as prescribed	by field rul		4-1-11-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-
Certification of per	rsonar knowredge ru	icilnation ba	ua:	
I hereby cerform, and that such				and facts placed on this
			Signature Signature	Missan
			Wahita Padilita	ng Corporation
			Company	& corporacion
Omeroday 188:3- 11		~ ~ ~ ~		
Operator Affidavit:				
(Note: Party making affida	vit must strike out inapplic	cable phrases, and		
Before me, the undersign known to me to be the pers	ned authority, on this day,			
identified in this instrument	that), and that such well was r	he is acting at th not intentionally d	e direction and on behalf eviated from the vertical	f of the operator of the well
				Title of Affiant
Sworn and Subs	cribed to before me	e, this the _	12th day o	of November
•				

INFORMATION AND INSTRUCTIONS AS PER STATEWIDE RULL 54

II. INCLINATION SURVEYS

A. Requirement of

- l. An inclination survey made by persons or concerns approved by the Commission shall be filed on a form prescribed by the Commission for each well drilled or deepened with rotary tools or when as a result of any operation the course of the well is changed.
- a. The first shot point of such inclination survey shall be made at a depth not greater than 500 feet below the surface of the ground and succeeding shot points shall be made either at 500 foot intervals or at the nearest drill bit change thereto; but not to exceed 1000 feet apart.
- 2. Inclination surveys conforming to these requirements may be made either during the normal course of drilling or after the well has reached total depth. Acceptable directional surveys may be filed in lieu of inclination surveys.
- 3. Copies of all directional or inclination surveys, regardless of the reason for which they are run, shall be filed as a part of or in addition to the inclination surveys otherwise required by this rule.

B. Reports

- 1. The report form prescribed by the Commission shall require that it be signed and certified by a party having personal knowledge of the facts therein contained.
- a. The report shall include a tabulation of the maximum drifts which could occur between the surface and the first shot point and each two successive shot points, assuming that all of the unsurveyed hole between any two shot points has the same inclination as that measured at the lowest shot point, and the total possible accumulative drift, assuming that all measured angles of inclination are in the same direction.
- 2. In addition, the report shall be accompanied by a sworn statement of the operator, or of someone acting at his direction on his behalf either, (1) that the well was not intentionally deviated from vertical whatsoever or, (2) that the well was deviated at random, with an explanation of the circumstances.
- 3. The report shall be filed in the District Office of the Commission for the district in which the well is drilled, by attaching one copy to each appropriate completion form for the well.
- 4. The Commission may require the submittal of the original charts, graphs, or discs resulting from the surveys.