

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
MEXICO 88240

Form approved
Budget Bureau No. 1004-0138
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-309376

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Continental USA Com *Fed*

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Lusk Strawn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6-TWN 19S-R32E

12. COUNTY OR PARISH

Lea

13. STATE

NM

1. SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
7990 IH 10 West, San Antonio, Tx 78230

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660 FSL + 1980 FEL

Unit Letter O, Section 6, Township 19S Range 32E
Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3671 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU R&O welding workover unit

Drop four sacks sand to cover perfs from 11,286 to 11,292.

RU NL McCollough to perforate well from 11,268 to 11,286 and from 11,146 to 11,158 with 2 JSPF from 3 1/8 csg. (62-.34" holes)

RU Halliburton and acidize well with 4000 gals 20% NEFE @ 6 bpm @ 3700 psi.

GIH and bail sand to open bottom perfs.

GIH with 2 3/8" tubing and 2" x 1.0625" x 24' insert pump.

Install beam pumping unit and put well on pump.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Senior Production Engineer

DATE 1/2/86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE 1-23-86

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

JAN 24 1986

002
JAN 24 1986