

COUNTY	LEA	FIELD	Undesignated	STATE	N.M.
OPR	TENNECO CORPORATION				MAP
	1 USA-Trigg-Federal				
	Sec. 8, T-19-S, R-32-E				CO-ORD
	1650' fr S Line & 1650' fr W Line of Sec.				
	Spud 10-25-63				
	Comp 2-16-64				
	CLASS		EL 3640		
	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING	LOG:				
13 3/8" 885' 750	Anhy 900				
8 5/8" 4006' 900	Yates 2710				
5 1/2" 12798' 550	7-R 2920				
	Del 5410				
	B Spg 7012				
LOGS EL GR RA IND HC A	Wolfe 10430				
	TD 12800', PBD 12725'				

IP Strawn Perfs 11503-509' Flwd 422 BOPD. Pot. Based on 20 hr test of 352 BO thru 13/64" chk., TP 2100#, gravity 46.4, GOR 2975.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 12,430' TYPE

F.R. 10-24-63
PD 12,430' - Strawn
10-28-63 TD 895', WOC.
11-4-63 TD 3535', fshg.
11-11-63 Drlg. 3688' lm.
11-18-63 Drlg. 3863' lm.
Had fishing job
11-26-63 Drlg. 4273' lm.
12-2-63 Drlg. 5279' lm.
12-9-63 Drlg. 7920' lm. & sh.
12-16-63 Drlg. 8855' lm.
12-30-63 TD 10376', lm. & sh., fshg.
DST (Bone Spring) 8990-9035', open 49 mins,
Rec 15' DM,
1 hr ISIP 85#, FP 21-21#, 1 hr FSIP 85#.
DST 9246-76', open 1 hr,
rec 3' oil + 30' DF,
59 min ISIP 1471#, FP 43-43#, 1 hr 30 min
FSIP 433#.

1-6-64 TD 11364', fshg. drill pipe.
1-13-64 Drlg. 11467' lm. & sh.
1-20-64 Drlg. 11842' lm. & sh. (Tight)
Cored 11495-521', rec 26' lm., w/fair poro. &
fair show throughout.
Cored 11521-551', rec 26' being:
3' lm., w/fair poro. & show, 23' dns blk.
lm.
DST 11468-551', pkr failed.
Re-DST 11454-551', open 3½ hrs,
Used 1000' WB, GTS in 25 mins, FTS in 2 hrs
5 mins, OTS in 2 hrs 10 mins, flwd 18.5 BO
in 45 mins thru 1/2" chk., SFP 350#, grvty
48.9, GOR 1925, rev out full string of oil,
rec 3 gals DM below sub,

1 hr ISIP 5252#, FP 789-1528#,
1 hr FSIP 5209#.
1-27-64 Drlg. 12544' lm., sh. & sd., tight.
2-3-64 TD 12800', WOC., tight.
2-10-64 TD 12800', tstg., tight.
2-17-64 TD 12800', tstg., tight.
2-24-64 TD 12800', PBD 12725', tight.
3-2-64 TD 12800', PBD 12725', tight.
3-9-64 TD 12800', PBD 12725', tight.
4-20-64 TD 12800', PBD 12725', COMPLETED.
Perf (Morrow) 12408-412', 12437-438', 12443-
444', 12470-471', 12489-490', 12526-527',
12546-547', 12662-663', 12692-694' W/2 SPF
Ac. 200 gals (MA), swbd gas @ TSTM.
Morrow Zone 12408-694' Temp. Abd.
Perf (Strawn) 11503-509' W/4 SPF,
Ac. 1500 gals.
LOG TOPS. Strawn 11347'. Morrow 12027'.