COPY TO O. C. C. ...

----

U

Form 9–331 Dec. 1973	Form Approved.
UNITED STATES	Budget Bureau No. 42-R1424
DEPARTMENT OF THE INTERIOR	5. LEASE NM 23009
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	
1. oil gas g	8. FARM OR LEASE NAME Llano "A" Federal
well well X other	9. WELL NO.
2. NAME OF OPERATOR Coquina Oil Corporation	1
3. ADDRESS OF OPERATOR P. O. Drawer 2960 Midland, TX 79702	10. FIELD OR WILDCAT NAME N W LUSK
<ol> <li>LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)</li> </ol>	11. SEC., T., R., M., OR BLK. AND SURVEY OR
	AREA Sec. 8-19S-32E
AT SURFACE: 1980' FNL & 660' FWL	ter and the second s
AT TOP PROD. INTERVAL: Projected the same. AT TOTAL DEPTH: Projected the same.	12. COUNTY OR PARISH 13. STATE Lea NM
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO.
REPORT, OR OTHER DATA	
BEQUEST FOR THE ST	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 3-330.)
	change on Form 3-330.)
CHANGE ZONES H U. S. GEOLOGIO	CAL SURVEY
ABANDON • HOBBS, NEW	V MEXICO
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state a including estimated date of starting any proposed work. If well is dire measured and true vertical deuths for all markers work. If well is dire	all pertinent details
including estimated date of starting any proposed work. If well is dire measured and true vertical depths for all markers and zones pertinent t	ectionally drilled, give subsurface locations and
MI & RIPH and revence since let	to this work.)*
MI & RUPU and reverse circulating unit on Nov. 30 to 1000 psi, OK. With 7-7/8" bit drilled out com	, 1979. Installed BOP's Teste
up on casing patch to 1000 poi fam 20	ent paten 2448 -2515 Pressure
LO SHOP DING for at 31251 During	cro on priviled and washed
to 1000 psi, held for 30 minutes of	J. Fressured up on caring
wait for rotary rig to drill out shoe, wash to old	d TD and doppen to tout. Will
Horrow Sana.	a lot and deepen to test
Subsurface Safety Values Manager	
Subsurface Safety Valve: Manu. and Type	Set @ Ft
18. I hereby certify that the foregoing is true and connect	
SIGNED Seland many TITLE Drilling Manager	
CEDIED FOD DECORD	DATE Uec. 11, 1979
CEPTED FOR RECORD	
CONDITIONS OF APPROVAL LE ANY	DATE
DF01% 1979	
GEOLOGICAL SURVEY	가 있는 것은 가 있는 것 같은 것 같이 있는 것이 있다. 이 가 있는 것은 것 같은 것 있는 것 같이 있다. 이 가 있는 것 같은 것 있는 것 같은 것 같이 있다.
ODDS, NEW MEXICO	
*See Instructions on Reverse Side	$\mathcal{A} = \{\mathcal{A}_{i}\}_{i=1}^{n}$