

State of New Mexico "L" No. 9

Spudded 11" Hole at 8:30 P. M. October 21, 1964.  
Ran 1448' of 8 5/8" O. D. Casing and cemented at  
1462' with 400 Sx. Class "C" 4% gel, and 250 Sx.  
Class "C" neat, (last 50 Sx. with 2% CACL). Plug  
at 1432'. Cement Circulated. Tested before and  
after drilling plug for 30 minutes 600 P. S. I.  
Tested O. K. Job complete 9:00 A. M. October 24,  
1964.

Ran 6836' of 2 7/8" O. D. Casing and cemented at  
6849' with 500 Sx. Incor 8% gel with FRA and 400  
Sx. Incor 4% gel. Plug at 6840'. Tested for 30  
minutes with 1500 P. S. I. Tested O. K. Job  
complete 10:00 A. M. November 10, 1964.

Perforate 2 7/8" O. D. Casing with one jet shot at  
6053', 6057', 6061', and 6067'. Acidize with 500  
gals acetic acid. Swab well. Re-acidize with 1000  
gals 15% NE acid.

On 12 Hour Potential Test ending 7:00 A. M. November  
12, 1964, well flowed through 14/64" choke, 90 BBL  
Oil, and No water.

GOR - 484

GRAVITY - 38.6

TOP OF PAY - 6053'

BTM OF PAY - 6067'

NMOCC DATE - November 8, 1964.

TEXACO Inc. DATE - November 12, 1964.