

GETTY OIL COMPANY
STATE "AN" NO. 8
SECTION 7 - T18S - R35E UNIT LETTER P
330' FSL & 330' FEL
TD 11833 DEVONIAN

13 3/8" 35.5# set @ 340' with 350 sxs circulated
9 5/8" 36# set @ 3458' with 1992 sxs circulated
4 1/2" 11.6# set @ 11832' with 170 sxs
2 7/8" 6.4# set @ 11037' with 1490 sxs TOC 5150' TS

perf. 4 1/2" csg. @ 11615 - 11660
perf. 2 7/8" csg. @ 10936 - 10948, 10014 - 10058

Set CIBP in 2 7/8" @ 9986' + 9' cmt.
Set CIBP in 4 1/2" @ 11400' + 20' cmt
Shot and pulled 2 7/8", and 4 1/2" @ 5190'
Set 25 sx plug across 2 7/8", and 4 1/2" csg. stubs
Set 50 sx plug @ 9 5/8" csg. shoe (3340 - 3500)
Set 10 sx plug @ surface
P & A

GETTY OIL COMPANY
STATE "AN" NO. 9
SECTION 7 - T18S - R35E UNIT LETTER I
1650' FSL & 330' FEL
TD 11793 DEVONIAN

13 3/8" 36# set @ 344' with 350 sxs circulated
8 5/8" 24, & 32# set @ 4857' with 3840 sxs TOC 500' TS
5 1/2" 15.5, 17# set @ 11792' with 519 sxs TOC 5865' TS

perfs. 11501 - 11577

Set 25 plug @ 7190 - 6940
Shot and pulled 5 1/2" csg @ 5940'
Set 25 sx plug across 5 1/2" csg stub @ 5940'
Set 25 sx plug @ 8 5/8" csg shoe (4775 - 4875)
Set 50 sx plug @ 815 - 915
Set 10 sx @ surface
P & A