

COUNTY	LEA	FIELD Wildcat	STATE NM
WC OPR	LONE STAR PRODUCING COMPANY		MAP
1 Golden, P. H. et al			
Sec. 7, T-18-S, R-38-E			CO-ORD
1830' fr S Line & 660' fr W Line of Sec.			
Spud 12-9-64		CLASS	EL 36938
P & A 2-10-65		FORMATION	DATUM
CSG & SX - TUBING	LOG:	Anhy 1695	
10 3/4" 426' 300		T/Salt 1792	
7 5/8" 3620' 750		B/Salt 2763	
5 1/2" 7654' 700		Yates 2908	
		7-R 3185	
		Queen 3750	
LOGS EL GR RA IND HC A		Gryb 4123	
		TD 8022'	

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	8100'	TYPE
DATE			

F.R. 11-27-64; Oper's Elev. 3693' Df
PD 8100' - Abo

12-14-64 Drlg. 2545' anhy & salt.

12-21-64 Drlg. 4356' 1m.

1-4-65 TD 6119', drlg cement @ 6059'.
Lost circ @ 6068'.

1-11-65 Drlg. 6989' dolo.

1-18-65 TD 7632', lost circ.
Lost circ. @ 7587'
Dry drilled to 7632'.

1-25-65 Drlg. 8018' dolo.

2-1-65 TD 8022', PBD 7643', swbg.
EST 7846-8022', open 1 hr 10 mins,
rec 900' DM + 5936' sul wtr,
1 hr ESIP 3059#, FP 762-762#,
1 hr 30 min FSIP 3059#.

2-1-65 - cont. -
SP DST 7654-98', open 55 mins,
rec 75' DM + 700' sul wtr,
1 hr ISIP 3039#, FP 292-1002#,
1 hr 30 min FSIP 2914#.
Set Retainer @ 7643'
Squeezed open hole 7654-8022' W/100 sx.
Perf @ 7100' W/4 SPF
Squeezed perf @ 7100' W/250 sx.
Re-Squeezed Perf @ 7100' W/450 sx.
Perf @ 7600' W/4 shots
DST @ 7600', open 40 mins,
rec 210' drlg mud
1 hr ISIP 654#, FP 142-142#,
1 hr FSIP 400#.

2-8-65 Ac. 500 gals @ 7600'
Swbd sul wtr
TD 8022', PBD 7500', swbg.
Swbd 10 B Sul Wtr Per Hr from perf @ 7600'
Set Retainer @ 7500'
Squeezed Perf @ 7600' W/100 sx.
Perf @ 7261', 7263', 7271', 7274' W/2 SPI
Ac. 1000 gals.
Swbd salty sul wtr
Squeezed perfs 7261-74' W/100 sx.
Perf @ 5800' W/4 shots
Squeezed Perf @ 5800' W/100 sx.
Perf 5776-80' W/2 SPF
Ac. 500 gals., swbd dry
Re-Ac. 1500 gals. 5776-80'
Swbd dry

2-8-65 - cont. -
Perf 5404-10' W/2 SPF
Ac. 1000 gals.
Swbd sul wtr, w/SSG for 5 hrs.
Squeezed perfs 5404-10' W/83 sx.
Perf 4595-97' W/2 SPF
Ac. 500 gals.
Swbd load & Acid Wtr, W/SSO & Swbd dry
Re-Ac. 2000 gals. 4595-97'
Swbd dry
Squeezed perfs 4595-97' W/150 sx.
Perf 4472-74', 4478-80', 4486-88', 4490-92',
4494-96' W/2 SPF
Ac. 1000 gals.
Swbd Acid Wtr, W/show gas for 14 hrs.

2-15-65 TD 8022', PLUGGED & ABANDONED.
Swbd 100% water from perfs 4472-96'
Set Retainer @ 4445'
Squeezed perfs 4472-96' W/100 sx.
Perf 4336-39', 4364-68', 4378-82' W/2 SPF
Ac. 1000 gals.
Swbd dry
Squeezed perfs 4336-82' W/100 sx.
(Holding for tops)

2-22-65 TD 8022', Completion Reported.
LOG TOPS: San Andres 4370', Glorieta 5752',
Paddock 5846', Blinbry 6263', Tubbs 6697',
Drinkard 7033', Abo 7450'.