

(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

REMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
LC-071856-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
**GREENWOOD PREGRAYBURG
OPERATING AREA**

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Lusk Stratum

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

6-19-32 N.M.P.M.

12. COUNTY OR PARISH 13. STATE

LEA

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ **DRILLING**
2. NAME OF OPERATOR
Am. American Petroleum Corp.
3. ADDRESS OF OPERATOR
Box 68, Hobbs, N.M. 88240
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

CGO' FSL X 2012' FWL, Sec. 6 (UNIT N, SE/4 SW/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether LF, RT, GR, etc.)

3667' RDB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Well was drilled to a depth of 11,410' without encountering oil or gas. Logs and DST confirmed Dry Hole. Pursuant to telephone approval of 2-5-65, Messrs A. R. Brown & J. W. Mark, the well is to be plugged and abandoned as follows: Spot 50 5x cement plugs at intervals 11,100'-11000'; 8,600'-8500'; 7,000'-6900'; 4,400'-4300'; in and out of 8 7/8" casing at 314', and a 10 5x plug at surface with P & A marker. All intervals to be filled with heavy mud laden fluid. Major clean up and restore ground conditions.

18. I hereby certify that the foregoing is true and correct

SIGNED

Original Signed By

M. E. STALEY

TITLE

Area Supt.

DATE

2-8-65

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

*See Instructions on Reverse Side

FEB 15 1965

**J. L. GORDON
ACTING DISTRICT ENGINEER**

DIST (040)

5-USGS 1-JWB
1-Conoco 1-Susp
1-Shell 1-WS
1-Carper 1-Guy
2-Union 1-Solomon
2-Geo