

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPL
(Other instructions
verse side)E*
re-Form approved.
Budget Bureau No. 42-R1424.GEOLOGICAL SURVEY
HOBBES OFFICE D. C. C.

5. LEASE DESIGNATION AND SERIAL NO.

LC-071856-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill deep reservoirs or to different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME GREENWOOD PRE-GRADING OPERATING AREA FEDERAL
2. NAME OF OPERATOR Pan American Petroleum Corp.	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR Box 68 Hobbs New Mexico 88240	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL X 1980' FEL, Sec. 7 (Unit B, NW/4, NE/4)	10. FIELD AND POOL, OR WILDCAT Lusk STRAWN
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 7-19-32 N M P M
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3655' R.D.B.	12. COUNTY OR PARISH Lea
	13. STATE N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In an effort to increase productivity propose to perforate 11,225-11,260 w/ 2 TSPF. Spot 500 lbs. of moth balls across perforations 11,264-76. Spot 15% acid over perforations 11,225-60. Acidize with 5,000 gallons.

Latest test - 5-10-68, pumped 4.5 BO X 0 BW in 24 hours.

TD-11,431'

PBD-11,361'

5 1/2" CSA-11,431

PERFS-11,264-76' w/ 2 TSPF

(Verbal auth. Mr. A. R. Brown to E. T. Snook 6-7-68)

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

+4 - USGS - H
1 - NSW
1 - SWS
1 - RY

*See Instructions on Reverse Side

JUN 10 1968
A. R. BROWN
DISTRICT ENGINEER