

LUSK SEVEN RIVERS UNIT WELL NO. 4
 (Previously Shell Federal "A" No. 3)
 660' FWL and 1980' FSL, Section 3, T19S, R32E
 Lea County, New Mexico

8 5/8" O.D., 24 LB./FT. CSG.
 Set @ 335' w/125 sx. in an 11" hole.
 (Top of cmt. @ surf. by circ.)

2 3/8" O.D., 4.7 LB./FT. TBG.

7 9 11 13 15 HOLE SIZE - INCHES 10 API/CD 100 API RADIATION INTENSITY INCREASES		233 235 245 246 250 260 270 281 290 DENSITY IN GM/CM ³ 46,140 CPH 1538 CPM/CD 15,380 CPH	
GAMMA RAY & CALIPER		DEPTH	DENSITY
Company	CACTUS DRILLING COMPANY	Drillers T.D.	3860'
Well	SHELL "A" FEDERAL NO. 3	Lane-Wells F.R.	3849'
Field	WILDCAT (QUEEN)	Lane-Wells T.D.	3851'
County	LEA	Elevations:	
State	NEW MEXICO	K.B. 3674' D.F. 3673' G.L. 3662.5'	

Proposed top of packer @ 3666'
 (Baker Model AD Tension)

Perf. 3816-20 w/4 s.p.f.

P.B.T.D. 3847'

4 1/2" O.D., 10.5 LB./FT. CSG.
 Set @ 3860' w/200 sx. in a 7 7/8" hole.

