

|                              |                         |           |             |           |       |
|------------------------------|-------------------------|-----------|-------------|-----------|-------|
| COUNTY                       | LEA                     | FIELD     | Wildcat     | STATE     | NM    |
| WC OPR                       | CACTUS DRILLING COMPANY |           |             |           | MAP   |
| 1 Shell-Federal              |                         |           |             |           |       |
| Sec. 3, T-19-S, R-32-E       |                         |           |             |           |       |
| 1980' fr S & E Lines of Sec. |                         |           |             |           |       |
| Spud 1-17-65                 |                         |           |             |           |       |
| Comp 3-21-65                 |                         |           |             |           |       |
|                              |                         | FORMATION | DATUM       | FORMATION | DATUM |
| CSG & SX - TUBING            |                         | LOG:      |             |           |       |
| 8 5/8"                       | 1324'                   | 300       | Anhy 1297   |           |       |
| 7"                           | 3991'                   | 125       | B/Salt 2780 |           |       |
|                              |                         |           | Yates 2995  |           |       |
|                              |                         |           | 7-R 3481    |           |       |
|                              |                         |           | Queen 3925  |           |       |
| LOGS EL GR RA IND HC A       |                         |           |             |           |       |
| TD 4203', PBD 3920'          |                         |           |             |           |       |

IP Seven Rivers Perfs 3851-61' Flwd 42 BOPD. Pot. Based on 24 hr test thru 1/2" chk., TP 60#, CP Pkr.

Distribution limited and publication prohibited by subscribers' agreement.  
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

|                 |                  |      |
|-----------------|------------------|------|
| CONT. Co. Tools | PROP DEPTH 4500' | TYPE |
| DATE            |                  |      |

F.R. 1-14-65; Oper's Elev. 3682' Df.  
PD 4500' - San Andres  
Contractor - Company Tools

1-18-65 Drlg. 865'.  
1-25-65 Drlg. 1950'.  
2-1-65 Drlg. 3040'.  
2-8-65 Drlg. 3542' dolo.  
2-15-65 Drlg. 3805'.  
900' water in hole @ 3765'.  
2-22-65 Drlg. 3902'.  
Slight show oil @ 3864'.  
3-1-65 TD 3991', WOC.  
3-8-65 Drlg. 4203'.  
3-15-65 TD 4203', PBD 3920', flwg load.  
Water @ TD.  
Perf 3851-61', 3925-32', 3957-60' W/2 SPF  
Ac. 500 gals. (3925-60')

3-15-65 - cont. -  
Swbd dry from perfs 3925-60'.  
Set BP @ 3920'  
Ac. 500 gals. (3851-61')  
Frac 20,000 gals oil + 23,000# sd. (3851-61')  
3-22-65 TD 4203', PBD 3920', COMPLETED.  
SAMPLE TOP: Queen 3926'.