

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

AUG 6 3 35 PM '65

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-9202	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name Superior "A" State
2. Name of Operator Hanagan Petroleum Corporation	8. Farm or Lease Name 1
3. Address of Operator P. O. Box 1737, Roswell, New Mexico	9. Well No. Wildcat
4. Location of Well UNIT LETTER L , 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 2 TOWNSHIP 18-S RANGE 35-E NMPM.	10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3925 KB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER **Production tests** ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/1 & 8/2/65 - Perforated 10159-164 with 4 shots/ft. (Schlumberger), acidized with 500 gal. NA, swab back load oil and acid water, swab dry. Reacidized with 1,000 gals. NE, swab back water & load oil,
8/3 & 8/4/65 - Swab dry. Set permanent type Johnston wasp bridge plug @ 10,000'. P.B. 10,000', perf. 34 holes: 9726, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 49, 52, 54, 56, 58, & 9760 (Schlumberger), acidized with 500 gal. NA, swab acid water & load oil (54 bbls.) plus estimated 25 bbls. slightly salty sulphur water in 10 hrs.
8/5 & 8/6/65 - P.B. 9600' Johnston wasp permanent bridge plug, perf. 40 holes: 9010, 12, 14, 16, 18, 20, 22, 24, 26 & 9038, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, A/500 NA, Flowed 75 bbls. oil 6 hrs. on 16/64" choke, FTP 500%, GOR 750:1, Gvty 37.1 - IPF 300 BOPD on 16/64"

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Hugh C. Hanagan TITLE Vice President DATE Aug 6, 1965

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: