*ubmit 3 Copies To Appropriate District State of New Mexico Form C-103 Office Revised March 25, 1999 Energy, Minerals and Natural Resources District 1 WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 District II 30-025-21276 OIL CONSERVATION DIVISION 811 South First, Artesia, NM 88210 5. Indicate Type of Lease District III 2040 South Pacheco STATE 1000 Rio Brazos Rd., Aztec, NM 87410 FEE Santa Fe, NM 87505 District IV State Oil & Gas Lease No. 2040 South Pacheco, Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: C.A. Taylor Oil Well Gas Well Other Injection Well 2. Name of Operator 8. Well No. Avra Oil Company POTrache or Wildcat 3. Address of Operator P.O. Box 3193, Midland, Texas 79702 Canyon Queen 4. Well Location Unit Letter P : 990 feet from the South line and 660 feet from the East line Lea County Range 38E Section Township 185 NMPM 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3637 DR 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS, 6 9 10 11 72 7 TEMPORARILY ABANDON ☐ CHANGE PLANS PLUG AND ABANDONMÉN PULL OR ALTER CASING ☐ MULTIPLE CASING TEST AND COMPLETION **CEMENT JOB** OTHER: OTHER: × 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 5-7-98 MIRU Pool Company, unseated 4 1/2" Loc-set, TOH w/ 129 Jrs of lined tbg. TIH w/ notched collar and 129jts, added 5 more jts. Cleaned out csg to 4114'. TOH w/ tbg. TIH w/ 3 1/8" perf gun. Added new perfs from 4090'-4100' (old perf 4095' sand notched). Perfed 10ft, 4 s/ft total 40 holes. 5-8-98 TIH w/ 4 1/2" loc-set plastic coated packer and 129 salta lined tbg, cir hole w 2% HCL and packer fluid. Set packer, acidized new perfs w/750 gals of 15% HCL. Tested csg to 500PSI, held OK. Lowered ijt pressure to 850 PDI. 7-22-98 MIRU Pool. Unseated packer, had a split collar 122 jts down. Replaced 1 jt, set loc-set w/ 129 jts @ 4023.20'. Ran csg integrity test to 550 PSI, held OK Comment: Original chart is attached. I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE President SIGNATURE ____ DATE 11-28-01 Type or print name Saeed Afghahi (915) 682-4866 Telephone No. (This space for State use)

TITLE

DATE

APPPROVED BY

Conditions of approval, if any:

