DISTRIBUTION SANTA FE FILE U.S.G.S. LAND OFFICE OPERATOR SUIDDW NOTES COMMISSION	Form C-103 Supersedes Old C-102 and C-103 Effective 1-1-65
U.S.G.S. LAND OFFICE OPERATOR	
U.S.G.S. LAND OFFICE OPERATOR	Ellective 1-1-65
LAND OFFICE OPERATOR	
OPERATOR	Sa. Indicate Type of Lease
	State X Fee
CLUDDY NOTICES	5. State Oil & Gas Lease No.
	384
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. 100 HOT USE THIS FORM FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
OIL X GAS OTHER-	7. Unit Agreement Name None
Manathan 0.3 Communication	8. Farm or Lease Name
Marathon O1 Company	State Warn A/C 2
Box 220 Hobbs, New Mexico	9. Well No. 15
Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER F 1650 FEET FROM THE NOTTH LINE AND 1650 FEET FROM	Undesignated Gloriet
THE WOST LINE, SECTION 6 TOWNSHIP 18 S RANGE 35 E NMPM.	
LINE, SECTION TOWNSHIP TOWNSHIP TOWNSHIP	
15. Elevation (Show whether DF, RT, GR, etc.)	12, County
3985' KDB (estimated)	Les
Check Appropriate Box To Indicate Nature of Notice, Report of Other	Doto.
NOTICE OF INTENTION TO: SUBSEQUENT	REPORT OF
	NET ON TOP.
PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
CHANGE PLANS CASING TEST AND CEMENT JQB	C
OTHER	
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including es	
Drilled 6-1/4" hole to 6285' T.D. May 10, 1965. Ran and	
4-1/2" 9.5# and 11.6#, J-55, ST&C, new casing from 11.20 with last setting depth including Baker Circulating Diffe and Baker Guide Shoe. The casing was cemented with 1150 (850 sacks Trinity litewate w/ 1/h# Flocele per sack and regular w/ 2% Gel). Cament circulated to surface. W.O.C. tested casing with 1500# pressure for 30 minutes. Held Company of the same same same same same same same sam	rential Collar sacks cement 300 sacks Trinity
with last setting depth including Baker Circulating Diffe and Baker Guide Shoe. The casing was cemented with 1150 (850 sacks Trinity litewate w/ 1/lu# Flocele per sack and regular w/ 2% Gel). Cament circulated to surface H O C	rential Collar sacks cement 300 sacks Trinity

CONDITIONS OF APPROVAL, IF ANY: