

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.

B-2519

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
3. Address of Operator	9. Well No.
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER <u>I</u> , <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM	<u>Undesignated</u>
THE <u>East</u> LINE, SECTION <u>3</u> TOWNSHIP <u>18-S</u> RANGE <u>35-E</u> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
<u>Later</u>	<u>Lea</u>

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

### SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Phillips Petroleum Company Rig No. 18, spudded 12:01 A.M., October 12, 1965. Drilled 12 1/4" hole to 485', reamed to 17 1/2" hole 0 to 333'. Set 13 3/8" 48# casing at 333'. P-J cemented with 400 sacks Trinity regular w/2% CaCl<sub>2</sub>, w/200# Tufplug in first 100 sacks. Pumped plug to 307' with 400#. Circulated 15 sacks cement. WOC 18 hrs, tested with 1500# for 30 minutes, ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] (W.J. Mueller) TITLE Associate Reservoir Engineer DATE 10-13-65

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: