orm 3160-5 August 1999)	UNITED STATE		N.M. OII 1625 N.	French [DY. FORM APPROVED	
100000 1	DEPARTMENT OF THE I		Hobbs,	NM 882	ONB No. 1004-0135 40 Expires November 30, 2000	
SUND	BUREAU OF LAND MANA RY NOTICES AND REPO		S. L	5. Lease Serial No.		
Do not use	this form for proposals to	drill or to re-	enter an		NMNM23006 Indian, Allottee or Tribe Name	·
abandoned	vell. Use Form 3160-3 (APL	0) for such pro	iposais.			
SUBMIT IN T	RIPLICATE - Other instru	uctions on re	verse side	7. 16	Unit or CA/Agreement, Name and	d/or No
I. Type of Weil	······································		· · · · · · · · · · · · · · · · · · ·			
Oil Well Gas Well	Other Re-Entry			8. V	Vell Name and No.	
2. Name of Operator				!	Moleen Federal	
Beach Exploration, Inc. 3a. Address		3b Phone No	(include area code)		PI Well No.	
800 N. Marienfeld Ste. 2	00, Midland, TX 79701	915/683-62			0-025-21400 ield and Pool, or Exploratory Area	·······
	c., T., R., M., or Survey Description				oung, San Andres South	
660' FSL & 660' FEL SE/4 SE4 Unit P					ounty or Parish, State	
Sec. 31, T18S, R32E				L	Lea Co., NM	
	PPROPRIATE BOX(ES) TO	INDICATE N	ATURE OF NOT	TICE, REPORT	, OR OTHER DATA	
TYPE OF SUBMISSION			TYPE OF ACTI			
Notice of Intent	C Acidize	Deepen	Product	tion (Start/Resume) Water Shut-Off	
Notice of Intent		Fracture Treat		ation	Well Integrity	
	Casing Repair	New Construc	tion 🔲 Recomp	olete	Other	
Subsequent Report						
Final Abandonment Notice Describe Proposed or Complete If the proposal is to deepen dirt Attach the Bond under which t following completion of the invite testing has been completed. Fi determined that the sile is ready	Change Plans Convert to Injection Convert to Injection d Operation (clearly state all pertin ctionally or recomplete horizontally he work will be performed or provi volved operations. If the operation nal Abandonment Notices shall be for final inspection.)	Plug and Abar Plug Back ent details, includi y, give subsurface ide the Bond No. c results in a multipl filed only after all	ndon Tempor Water D ng estimated starting of locations and measure on file with BLM/BLA	arily Abandon Disposal date of any propos ed and true vertical A. Required subse	Re-entry ed work and approximate duration I depths of all pertinent markers ar guent reports shall be filed within	nd zone 1 30 da
 Final Abaadonment Notice Describe Proposed or Complete If the proposal is to deepen dird Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the sile is ready Rigged up, drilled out Drilled out cement plut 1713'-1900', 8 5\8" csg s Pulled out, picked up down to 5325'. Ran logs 5300'-3194'' 5. Ran 7" 23# J-55 8RD Ran 4 1/2" 11.6# J-55 Perforated San Andres 	Change Plans Convert to Injection d Operation (clearly state all pertin ctionally or recomplete horizontally he work will be performed or provious volved operations. If the operation nal Abandonment Notices shall be for final inspection.) surface plug in 13 3/8" csg, ugs w/6 3/4" bit, 13 3/8" shoe	Plug and Abar Plug Back ent details, includi y, give subsurface ide the Bond No. c results in a multipl filed only after all tested BOP. e plug 621'-700' trilled open hold al Laterolog. //650sx circulat nted w/350 sx T s)	ndon Tempor Water D Water D Nocations and measure occations and measure is bocations and measure on file with BLM/BLA e completion or recom requirements, includ , open hole plug 9 e plug 3655'-3890 e plug 3655'-3890 red 225 sx to pit. FOC @ 3808' by C	arily Abandon Disposal date of any proposed and true vertical the Required subset ing reclamation, a D99'-1080', top by open hole plu ACCEPT BL.	Re-entry red work and approximate duration I depths of all pertinent markers ar quent reports shall be filed within interval, a Form 3160-4 shall be fi nave been completed, and the open of 8 5/8" csg stub plug	nd zone 1 30 da iled on rator h
 Final Abaadonment Notice Describe Proposed or Complete If the proposal is to deepen dirt Attach the Bond under which t following completion of the invitesting has been completed. Fi determined that the site is ready Rigged up, drilled out Drilled out cement plu 1713'-1900', 8 5\8" csg s Pulled out, picked up down to 5325'. Ran 7" 23# J-55 8RD Ran 4 1/2" 11.6# J-55 Perforated San Andres Acidized w/7200 gal 1 	Change Plans Convert to Injection Convert to Injection d Operation (clearly state all pertin extionally or recomplete horizontally he work will be performed or provi volved operations. If the operation and Abandonment Notices shall be for final inspection.) surface plug in 13 3/8" csg, ugs w/6 3/4" bit, 13 3/8" shoe hoe plug 2895'-3220'. 7 7/8" bit, reamed to 3220', c GR, Neutron , Density & Du LT&C to 1108'. Cemented w 8RD LT&C to 5305', cemented 4973'-5009' 2 SPF (38 hole: 5% NEFE and swab tested, f	Plug and Abar Plug Back ent details, includi y, give subsurface ide the Bond No. c results in a multipl filed only after all tested BOP. e plug 621'-700' trilled open hold al Laterolog. //650sx circulat nted w/350 sx T s)	ndon Tempor Water D Water D Nocations and measure occations and measure is bocations and measure on file with BLM/BLA e completion or recom requirements, includ , open hole plug 9 e plug 3655'-3890 e plug 3655'-3890 red 225 sx to pit. FOC @ 3808' by C	arily Abandon Disposal date of any proposed and true vertical the Required subset ing reclamation, a D99'-1080', top by open hole plu ACCEPT BL.	Re-entry red work and approximate duration I depths of all pertinent markers ar quent reports shall be filed within interval, a Form 3160-4 shall be fil have been completed, and the open of 8 5/8" csg stub plug ug 4656'=4810' and washed ED FOR RECORD	nd zone 1 30 da iled on rator h
 Final Abaadonment Notice Describe Proposed or Complete If the proposal is to deepen dirt Attach the Bond under which t following completion of the invitesting has been completed. Fi determined that the site is ready Rigged up, drilled out Drilled out cement plu 1713'-1900', 8 5\8" csg s Pulled out, picked up down to 5325'. Ran 10gs 5300'-3194' 5. Ran 7" 23# J-55 8RD Ran 4 1/2" 11.6# J-55 Perforated San Andres Acidized w/7200 gal 1 	Change Plans Convert to Injection Convert to Injection d Operation (clearly state all pertin extionally or recomplete horizontally he work will be performed or provi volved operations. If the operation and Abandonment Notices shall be for final inspection.) surface plug in 13 3/8" csg, ugs w/6 3/4" bit, 13 3/8" shoe hoe plug 2895'-3220'. 7 7/8" bit, reamed to 3220', c GR, Neutron , Density & Du LT&C to 1108'. Cemented w 8RD LT&C to 5305', cemented 4973'-5009' 2 SPF (38 hole: 5% NEFE and swab tested, f	Plug and Abar Plug Back ent details, includi y, give subsurface ide the Bond No. c results in a multipl filed only after all tested BOP. e plug 621'-700' trilled open hold al Laterolog. 1/650sx circulat nted w/350 sx T s) 2-3 BOPD. No	ndon Tempor	arily Abandon Disposal date of any proposed and true vertical the Required subset ing reclamation, a D99'-1080', top by open hole plu ACCEPT BL.	Re-entry red work and approximate duration I depths of all pertinent markers ar quent reports shall be filed within interval, a Form 3160-4 shall be fil have been completed, and the open of 8 5/8" csg stub plug ug 4656'=4810' and washed ED FOR RECORD	nd zone 1 30 da iled on rator h
 Final Abaadonment Notice Describe Proposed or Complete If the proposal is to deepen dird Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the sile is ready Rigged up, drilled out Drilled out cement plut 1713'-1900', 8 5\8" csg s Pulled out, picked up down to 5325'. Ran logs 5300'-3194' is Ran 7" 23# J-55 8RD Ran 4 1/2" 11.6# J-55 Perforated San Andress Acidized w/7200 gal 1 	Change Plans Convert to Injection Convert to Injection d Operation (clearly state all pertin extionally or recomplete horizontally he work will be performed or provi volved operations. If the operation and Abandonment Notices shall be for final inspection.) surface plug in 13 3/8" csg, ugs w/6 3/4" bit, 13 3/8" shoe hoe plug 2895'-3220'. 7 7/8" bit, reamed to 3220', c GR, Neutron , Density & Du LT&C to 1108'. Cemented w 8RD LT&C to 5305', cemented 4973'-5009' 2 SPF (38 hole: 5% NEFE and swab tested, f	Plug and Abar Plug Back ent details, includi y, give subsurface ide the Bond No. c results in a multipl filed only after all tested BOP. e plug 621'-700' trilled open hold al Laterolog. //650sx circulat nted w/350 sx T s)	ndon Tempor	arily Abandon Disposal date of any proposed and true vertical the Required subset ing reclamation, a D99'-1080', top by open hole plu ACCEPT BL.	Re-entry red work and approximate duration I depths of all pertinent markers ar quent reports shall be filed within interval, a Form 3160-4 shall be fil have been completed, and the open of 8 5/8" csg stub plug ug 4656'=4810' and washed ED FOR RECORD	nd zone 1 30 da iled on rator h
 Final Abaadonment Notice Describe Proposed or Complete If the proposal is to deepen dirt Attach the Bond under which t following completion of the invitesting has been completed. Fi determined that the site is ready Rigged up, drilled out Drilled out cement plu 1713'-1900', 8 5\8" csg s Pulled out, picked up down to 5325'. Ran 7" 23# J-55 8RD Ran 4 1/2" 11.6# J-55 Perforated San Andres Acidized w/7200 gal 1 	Change Plans Convert to Injection Convert to Injection d Operation (clearly state all pertin ectionally or recomplete horizontally he work will be performed or provi volved operations. If the operation and Abandonment Notices shall be for final inspection.) surface plug in 13 3/8" csg, ugs w/6 3/4" bit, 13 3/8" shock hoe plug 2895'-3220'. 7 7/8" bit, reamed to 3220', c GR, Neutron , Density & Du LT&C to 1108'. Cemented w 8RD LT&C to 5305', cemented 4973'-5009' 2 SPF (38 hole: 5% NEFE and swab tested, steries and correct	Plug and Abar Plug Back ent details, includi y, give subsurface ide the Bond No. c results in a multipl filed only after all tested BOP. e plug 621'-700' drilled open hold al Laterolog. 1/650sx circulat nted w/350 sx T s) 2-3 BOPD. No Title Date	ndon Tempor Water D Water D Note that the starting of locations and measure on file with BLM/BLA is completion or recom requirements, includ d open hole plug 9 e plug 3655'-3890 ted 225 sx to pit. FOC @ 3808' by C n commercial.	arily Abandon Disposal date of any proposed and true vertical Required subsempletion in a new ing reclamation, a D99'-1080', top ', open hole plu AUCEPT BL. JA. CAR	Re-entry red work and approximate duration I depths of all pertinent markers ar quent reports shall be filed within interval, a Form 3160-4 shall be fil have been completed, and the open of 8 5/8" csg stub plug ug 4656'=4810' and washed ED FOR RECORD	nd zone 1 30 da iled on rator h
 Final Abaadonment Notice Describe Proposed or Complete If the proposal is to deepen dird Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the sile is ready Rigged up, drilled out Drilled out cement plut 1713'-1900', 8 5\8" csg s Pulled out, picked up down to 5325'. Ran logs 5300'-3194' is Ran 7" 23# J-55 8RD Ran 4 1/2" 11.6# J-55 Perforated San Andress Acidized w/7200 gal 1 	Change Plans Convert to Injection Convert to Injection d Operation (clearly state all pertin ectionally or recomplete horizontally he work will be performed or provi volved operations. If the operation and Abandonment Notices shall be for final inspection.) surface plug in 13 3/8" csg, ugs w/6 3/4" bit, 13 3/8" shock hoe plug 2895'-3220'. 7 7/8" bit, reamed to 3220', c GR, Neutron , Density & Du LT&C to 1108'. Cemented w 8RD LT&C to 5305', cemented 4973'-5009' 2 SPF (38 hole: 5% NEFE and swab tested, steries and correct	Plug and Abar Plug Back ent details, includi y, give subsurface ide the Bond No. c results in a multipl filed only after all tested BOP. e plug 621'-700' drilled open hold al Laterolog. 1/650sx circulat nted w/350 sx T s) 2-3 BOPD. No Title Date	ndon Tempor	arily Abandon Disposal date of any proposed and true vertical Required subsempletion in a new ing reclamation, a D99'-1080', top ', open hole plu AUCEPT BL. JA. CAR	Re-entry red work and approximate duration I depths of all pertinent markers ar quent reports shall be filed within interval, a Form 3160-4 shall be fil have been completed, and the open of 8 5/8" csg stub plug ug 4656'=4810' and washed ED FOR RECORD	nd zone 1 30 da iled on rator h
 Final Abaadonment Notice Describe Proposed or Complete If the proposal is to deepen dird Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the sile is ready Rigged up, drilled out Drilled out cement plut 1713'-1900', 8 5\8" csg s Pulled out, picked up down to 5325'. Ran logs 5300'-3194' is Ran 7" 23# J-55 8RD Ran 4 1/2" 11.6# J-55 Perforated San Andress Acidized w/7200 gal 1 	Change Plans Convert to Injection Convert to Injection d Operation (clearly state all pertin ectionally or recomplete horizontally he work will be performed or provi volved operations. If the operation and Abandonment Notices shall be for final inspection.) surface plug in 13 3/8" csg, ugs w/6 3/4" bit, 13 3/8" shock hoe plug 2895'-3220'. 7 7/8" bit, reamed to 3220', c GR, Neutron , Density & Du LT&C to 1108'. Cemented w 8RD LT&C to 5305', cemented 4973'-5009' 2 SPF (38 hole: 5% NEFE and swab tested, steries and correct	Plug and Abar Plug Back ent details, includi y, give subsurface ide the Bond No. c results in a multipl filed only after all tested BOP. e plug 621'-700' drilled open hold al Laterolog. 1/650sx circulat nted w/350 sx T s) 2-3 BOPD. No Title Date	ndon Tempor Water D water D No file with BLM/BLA e completion or recom requirements, includ completion or recom recompletion or recom recompletion or recom requirements, includ completion or recom requirements, includ completion or recom recompletion or recom recom recompletion or recom recompletion or recompletion or recom recompletion or recom recompletion or recompletion or recom recompletion or recompletion or recom recompletion or recompletion or recomplet	arily Abandon Disposal date of any proposed and true vertical Required subsempletion in a new ing reclamation, a D99'-1080', top ', open hole plu AUCEPT BL. JA. CAR	Re-entry red work and approximate duration I depths of all pertinent markers ar quent reports shall be filed within interval, a Form 3160-4 shall be fil have been completed, and the open of 8 5/8" csg stub plug ug 4656'=4810' and washed ED FOR RECORD N 2 8 102 N 2 8 102 N COUFLEY	nd zone 1 30 da iled on rator h
 Final Abaadonment Notice Describe Proposed or Complete If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the sile is ready Rigged up, drilled out Drilled out cement plut 1713'-1900', 8 5\8" csg s Pulled out, picked up down to 5325'. Ran logs 5300'-3194' if S. Ran 7" 23# J-55 8RD Ran 4 1/2" 11.6# J-55 Perforated San Andres Acidized w/7200 gal 1 I hereby certify that the foregoin is the formation of the second second	Change Plans Convert to Injection Convert to Injection d Operation (clearly state all pertin ectionally or recomplete horizontally he work will be performed or provi volved operations. If the operation and Abandonment Notices shall be for final inspection.) surface plug in 13 3/8" csg, ugs w/6 3/4" bit, 13 3/8" shock hoe plug 2895'-3220'. 7 7/8" bit, reamed to 3220', c GR, Neutron , Density & Du LT&C to 1108'. Cemented w 8RD LT&C to 5305', cemented 4973'-5009' 2 SPF (38 hole: 5% NEFE and swab tested, steries and correct	Plug and Abar Plug Back ent details, includi y, give subsurface ide the Bond No. c results in a multipl filed only after all tested BOP. e plug 621'-700' trilled open hold al Laterolog. //650sx circulat nted w/350 sx T s) 2-3 BOPD. No Title R FEDERAL O	ndon Tempor Water D Water D No pen hole plug 9 e plug 3655'-3890 red 225 sx to pit. FOC @ 3808' by C n commercial. Production e Production e January 16, 20 R STATE OFFICI	arily Abandon Disposal date of any proposed and true vertical Required subsempletion in a new ing reclamation, a D99'-1080', top ', open hole plu AUCEPT BL. JA. CAR	Re-entry red work and approximate duration I depths of all pertinent markers ar quent reports shall be filed within interval, a Form 3160-4 shall be fil have been completed, and the open of 8 5/8" csg stub plug ug 4656'=4810' and washed ED FOR RECORD N 2 8 1002 N 2 8 1002	nd zone 1 30 da iled on rator h

•

X		_
li	2	